



GSZ 11-320 PERL

Straight grinder 32 500/min

Ergonomic, extremely powerful die grinder with high plunge depth for heavy-duty grinding and deburring in difficult-to-reach spots.

Product number: 7 223 22 60 00 0

Details

- + Long narrow neck allows tool to plunge a long way into workpieces (e.g. grinding inside pipes).
- User protection features include blockage monitoring, restart protection, soft start and electronic overload protection.
- Innovative collets with all-round flange to protect the workpiece and prevent the wrench sliding off during tool changes.
- + POWERtronic tachoelectronics for enormous power, power reserve and exceptional speed stability under load.
- + Removable rubber collar bearing cover.
- + Motor and electronics protected against metal dust.
- + Variable speed allows different tools to be used.

Price includes

- + 1 collet Ø 8 mm
- + Jaw spanner SW17

+ Jaw spanner SW13

Product feature

+ Long neck

Application



VIBRATION AND SOUND EMISSION

Cutting

Roughing-down

Grinding

Deburring

Brushing

+ suitable
+ well suitable

Technical data

TECHNICAL DATA

Input	1,010 W	Sound pressure level LpA Uncertainty of measured value	85 dB 3 dB
Output	620 W	КрА	
Speed, no load	9,500 - 32,500 rpm	Sound power level LWA Uncertainty of measured value KWA	96 dB 3 dB
Grinding wheel for max. Ø	45 mm	Sound peak value LpCpeak	98 dB
Collet for max. Ø	8 mm	Uncertainty of measured value KpCpeak	3 dB
Collar Ø	43 mm	Vibration value 1 αhv 3-	9,7 m/s²
Max. cutter diameter	12 mm	Way Uncertainty of measured value Kα	1,5 m/s²
Cable with plug	4 m		
Weight according to EPTA	2.10 kg		

VALUES

Application examples



