



WPO 14-25 E

Sander polisher

Extremely powerful sander/polisher for cool machining of stainless steel surfaces.

Product number: 7 221 49 00 23 0

Details

- + Extremely powerful even at low speeds thanks to mechanical gear reduction and FEIN high power motor.
- + Infinitely variable speed, ideal for sanding, satin finishing, brushing and high-gloss polishing of stainless steel.
- + Universal suitability as fully-functional sander, polisher and satin-finisher.
- + Excellent handling.
- + Spindle lock.
- + Right or left-handed operation.
- + Restart protection.
- + Soft start.
- + H 07 industrial cable.
- + Dustproof ball bearing.
- + Carbon brushes with self cut-off function.
- + Comprehensive range of accessories available.

Price includes

- + 1 anti-vibration handle

Product feature

- + Soft start
- + FEIN high-power motor
- + Restart protection
- + Spindle lock

Application

| | |
|---------------|----|
| Polishing | ++ |
| Rough sanding | ++ |
| Fine sanding | ++ |
| Dry sanding | ++ |
| Micro-sanding | ++ |

+ suitable
 ++ well suitable

Technical data

TECHNICAL DATA

| | |
|--------------------------|-----------------|
| Input | 1,200 W |
| Output | 750 W |
| Sanding pad Ø | 230 mm |
| Speed, no load | 900 - 2,500 rpm |
| Polishing disc Ø | 230 mm |
| Mounting thread | M 14 |
| Cable with plug | 4 m |
| Weight according to EPTA | 2.50 kg |
| Weight according to EPTA | 2.50 kg |

VIBRATION AND SOUND EMISSION VALUES

| | |
|--|---|
| Sound pressure level LpA Uncertainty of measured value KpA | 84 dB 3 dB |
| Sound power level LWA Uncertainty of measured value KWA | 95 dB 3 dB |
| Sound peak value LpCpeak Uncertainty of measured value KpCpeak | 100 dB 3 dB |
| Vibration value 1 α_{hv} 3-way Vibration value 2 α_{hv} 3-way | $\alpha_{h,P}$ 3,5 m/s ² $\alpha_{h,SG}$ 2,5 m/s ² |
| Uncertainty of measured value K α | 1,5 m/s ² |

Application examples

