



KBC 36 MAGFORCE

Structural Steel-Set 3/4 in

Weldon / HSS NOVA 25

The smallest core drill in the world with forward and reverse running coupled with a large number of HSS NOVA 25 core drilling accessories. Perfect for steel and bridge construction.

Product number: 7 273 23 64 00 0

Details

- + Extremely small and light for working in tight and difficult-to-reach spots – including vertically and overhead – thanks to height of 169 mm, a length of 290 mm and a weight of 8.5 kg.
- + Extremely low wear and long-life tool design with spindle sleeve feed without clearance for accurate drilling results in tough use in industry and manual trades.
- + Very powerful and maintenance-free brushless 1200 W high-power motor with high speed stability for continuously fast work progress as well as forward / reverse running and electronic speed setting for all drilling applications, such as core drilling, twist drilling and tapping and countersinking.
- + HSS NOVA 25 core drill bit: Long service life and particularly resistant to shock and impact: thanks to its tough cutting edges and outstanding HSS steel with a hardness of 64 HRC, the core drill bit is perfectly designed for tough use in steel construction and installation work.
- + L-BOXX system: Keep things stowed clearly, tidily and safely. Thanks to the tray for small parts, there is room for all accessories and the L-BOXXs can also be joined together and stacked with ease.

Price includes

- | | |
|--|---|
| + 1 magnetic core drill | + 1 x 1/2" ratchet |
| + 1 x 1/2" socket wrench extension | + 1 x coolant pump |
| + 1 lashing strap | + 1 swarf hook |
| + 1 x 82 mm centring pin | + 1 contact guard |
| + 1 additional handle | + 1 x 5 mm hexagon socket wrench |
| + 1 x 5 mm hexagon socket wrench with T-handle | + 1 plastic tool case (L-BOXX 238) |
| + HSS twist drills, 35 mm cutting depth (3 each of diameter 10 mm and 12 mm) | + HSS NOVA 25 core drill bits, 25 mm cutting depth (3 each of diameter 14 / 16 / 18 / 20 / 22 mm) |
| + 2 x 82 mm centring pin | + 1 cutting paste |
| + 1 L-BOXX 136 for accessories | |

Product feature

- | | |
|--|-----------------------|
| + Magnetic holding force display | + Reversible rotation |
| + Variable speed control | + Memory function |
| + Speed-controlled electronics (tacho) | + Tilt sensor |

Application



FEIN

Core drilling in metal with a Ø up to 35 mm

++

Working overhead

++

Installation work

++

+ suitable
++ well suitable

Technical data

TECHNICAL DATA

Input	1,200 W
Output	680 W
Speed, full load	130 - 610 rpm
Speed, no load	130 - 660 rpm
Carbide core drill bit max. Ø	36 mm
HSS core drill max. Ø	36 mm
Core drill, drilling depth max.	35 mm
Twist drill max. Ø	16 mm
Tapping	M 12
Countersinking max. Ø	32 mm
Core drill holder	3/4 in Weldon
Width across corners	40 mm
Height	169 mm
Length	290 mm

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Uncertainty of measured value KpA	95,3 dB 5 dB
Sound power level LWA Uncertainty of measured value KWA	103,3 dB 5 dB
Sound peak value LpCpeak Uncertainty of measured value KpCpeak	106,3 dB 5 dB
Vibration value 1 α_{hv} 3-way Uncertainty of measured value K α	ah,D = <2,5 m/s ² 1,5 m/s ²



FEIN

Stroke

46 mm

Height

169 mm

Cable with plug

3 m

Application examples

