



KBE 36 QW MAGSPEED

Endurance magnetic core drill for up to 36 mm

Small and lightweight single-speed endurance magnetic core drill offering unique performance and service life even under the most challenging conditions in the workshop and on the construction site.

Product number: 7 273 28 61 00 0

Details

- Twice the productivity combined with the perfect result: drilling times are halved, the work process is sped up. Thanks to rapid work progress, you can drill up to 60 holes rather than the 30 that used to be possible in the same time.
- Outstanding cutting performance that has never been seen before thanks to speed and torque curve with cutting speeds of up to 70 m/min, ideal for HM ULTRA and HM ULTRA SPEED core drill bits.
- Unique durability for up to 240 000 holes thanks to the extremely low-wear machine concept with

- brushless 1 600 W high-power motor and internal drill motor cable routing.
- + Good accessibility in cramped operating situations.
- + Convenient magnetic holding force display helps the user to reliably position the tool.
- + Tilt sensor stops the drill motor when the tool slips or tilts.
- + Integrated coolant tank delivers long core drill bit lives
- + Feed handwheel can be moved from one side to the other without any tools.
- + Personal safety switch.

Price includes

- + 1 magnetic core drill
- + 1 lashing strap
- + 1 contact guard

- + 1 coolant tank
- + 1 centring pin 100 mm
- + 1 case

Product feature

- + Magnetic holding force display
- + Feed handwheel can be moved from one side to the other
- Tilt sensor
- Tool-free core bit quick change system



Application



Core drilling in metal with a Ø up to 35 mm	++
Working overhead	++
Installation work	++
Workshop jobs	++
	+ suitable+ + well suitable
Technical data	
TECHNICAL DATA	
Input	1,600 W
Output	1,200 W
Motor	brushless
Speed, full load	620 rpm
Speed, no load	620 rpm
Carbide core drill bit max. Ø	36 mm
HSS core drill max. Ø	20 mm
Core drill, drilling depth max.	50 mm
Core drill holder	3/4 in Weldon
Changing the core bit	tool-free
Stroke	107 mm
Magnetic holding power	10,000 N
Magnetic foot dimensions	175 x 80 mm
Cable with plug	4 m





Application examples

















