



MULTIMASTER AMM 700 1.7 Q Joint Renovation

Battery-powered oscillating multi-tool

Our best MultiTool specially for grouting renewal with durable 12-star receptacle and 7 blades for cutting out elastic joints.

Product number: 7 129 37 64 00 0



Details

- Precision MultiTools get into hard-to-reach places. Thanks to vibration damping, they work quietly and precisely.
- → Versatility blade lengths up to 98 mm allow even very deep joints to be cut. The diamondcoated cleaning blade cleans mortar flanks before you fill them in again.
- + Safety and simplicity MultiTools work precisely and safely in the joint. Blades don't break and the power tool is protected against overload and overheating. Misuse is almost impossible.
- + Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- + QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.
- + 12-sided holder for optimum torque transfer.
- + 18 V FEIN PowerDrive motor: very powerful and virtually wear-free, brushless motor offering

- great efficiency, ability to handle extreme loads and a long service life.
- + Tacho generator: constant speeds even under load and infinitely variable electronic speed control.
- + Metal gearbox: ability to withstand high loading and outstanding service life because all the gearbox parts are made from metal.
- + Electronic Cell Protection (ECP): ECP protects against overload, overheating and total discharge.
- → The COOLPACK technology ensures a longer battery life and therefore makes long operating periods possible.
- + The battery charge can be read off the battery.
- Compatible with AMPShare/Bosch Professional
 18 V batteries.
- + Ideally equipped for every job. Mobile working with the L-BOXX system.

Price includes

- + 5 Cutter blades, straight (form 117) 6 390 31 17 01 5
- + 1 Cutter blade, mushroom shaped 6 390 31 28 01 2
- + 1 protective cover for tool changes
- + 1 plastic tool case (L-BOXX 238)
- + 1 Cutter blade, straight, long (form 116) 6 390 31 16 01 1
- + 1 handle
- + 1 sharpening stone (63719010014)

Technical data

TECHNICAL DATA

VIBRATION AND SOUND EMISSION VALUES

Battery voltage

18 V

Battery compatibility

Li-ion / ProCORE Li-ion

Sound pressure level LpA Uncertainty of measured value KpA 77,0 dB 3.0 dB



Battery interface

18 V AMPShare

10,000 - 19,500 rpm

Tool Holder

Oscillations

Tool change

Amplitude

Weight without storage battery

12-sided

QuickIN

2 x 1,7°

1.10 kg

Sound power level LWA Uncertainty of measured value KWA

Sound peak value LpCpeak Uncertainty of measured value KpCpeak

Uncertainty of measured value $K\alpha$

85,0 dB 3,0 dB

90,3 dB

3,0 dB

1,5 m/s²

Application examples



