



# MULTIMASTER MM 500 Plus

## Oscillating multi-tool – MM 500

The powerful MultiTool for rapid work progress (in interior work and renovation) with a bimetal saw blade for wood, metal and plastics.

Product number: 7 229 67 69 00 0

### Details

- + Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- + StarlockPlus tool mounting: more work progress and greater precision thanks to 100% power transmission without losses.
- + QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.
- + With the StarlockPlus tool mounting, you can access around 100 FEIN accessories from the Starlock and StarlockPlus performance classes.
- + 350 W FEIN motor. Powerful motor with a high copper content, which is suited to overload for a higher cutting speed and faster work progress.
- + Tacho generator: constant speeds even under load and infinitely variable electronic speed control.
- + Metal gearbox: ability to withstand high loading and outstanding service life because all the gearbox parts are made from metal.
- + Mechanical interface: for stationary operation in the table or drill jig holder or for securing the depth stop.
- + Industrial cable: large working radius thanks to finely stranded 5 metre rubber cable of industrial quality.
- + Ideally equipped for every form of use. Mobile working with the L-BOXX system.

### Price includes

- + 1 Universal E-Cut saw blade (44 mm)
- + 1 tool case (L-BOXX 136)

### Technical data

#### TECHNICAL DATA

Input

350 W

#### VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA  
Uncertainty of measured value  
KpA

75,6 dB  
3 dB



# FEIN

|                          |              |   |                 |
|--------------------------|--------------|---|-----------------|
| Oscillations             | - rpm        | Sound power level LWA<br>Uncertainty of measured value<br>KWA           | 83,6 dB<br>3 dB |
| Tool Holder              | StarlockPlus |   |                 |
| Tool change              | QuickIN      | Sound peak value<br>LpCpeak<br>Uncertainty of measured value<br>KpCpeak | 90,3 dB<br>3 dB |
| Amplitude                | 2 x 1,7°     |   |                 |
| Cable with plug          | 5 m          |   |                 |
| Weight according to EPTA | 1.40 kg      |   |                 |

## Application examples

