



F-IRON Cut 57 AS Set 2 x 8 Ah

Compact cordless circular saw for metal

Powerful cordless metal circular saw for rapid, precise cold cuts in sheet metals, pipes and profiles with a cutting depth of up to 57 mm. Including battery starter set of 2 x 8 Ah ProCORE batteries and rapid charger.

Product number: 7 136 04 62 00 0



Details

- + High performance low weight: 50% more material is removed than with standard metal circular saws as the brushless motor, ProCORE battery and optimally coordinated saw blade interact perfectly. And the tool weighs just 3 kg.
- + Housing and safety hood made from die-cast aluminium and swarf collecting vessel made from material with low flammability for maximum protection from hot metal chips with sharp edges. The user has an unobstructed view of the cutting line at all times thanks to the LED working lamp.
- → Pipes, profiles, metal grilles and sheet metals with a cutting depth of up to 57 mm can be sawn rapidly and precisely. Guide rail adapter for straight, long cuts compatible with guide rails from Makita, BOSCH, Festool, Mafell.
- → Manual speed setting (6 levels) for optimum results with a whole host of materials and no rework.
- + Cold cuts for cuts with virtually no sparks or burrs.
- + The LED light is activated in advance by the release switch.
- + Safety hood closes in < 0.3 s even after 50 000 cycles.

- + Better handling low weight, ergonomic handles including Softgrip for right- and left-handed users.
- + Electronic user protection: Efficient brake (0.2 s), temperature-based shutdown to avoid permanent damage to tool and battery, restart protection, dead man's switch.
- Large swarf collecting vessel made from material with low flammability for long intervals between emptying.
- + Heat-resistant, scratch-resistant and impactresistant housing made from die-cast aluminium.
- Compatible with all 18 V AMPShare ProCORE batteries and chargers for even more power and flexibility. Also suitable for 18 V Bosch Professional cordless devices.
- Maximum work progress with AMPShare 18V ProCORE batteries: COOLPACK 2.0 technology delivers a 135% longer battery life. State-of-theart cell technology and intelligent battery management deliver 87% more power than with conventional batteries. "Electronic Cell Protection" (ECP) protects the battery from overload, overheating and total discharge.
- + Ideally equipped for every form of use. Mobile working with the L-BOXX system.

Price includes

- 1 circular saw blade for construction steel
- + 1 socket head wrench 5 mm
- + 1 parallel stop
- + 1 x GAL18 V-160 AS rapid charger

- + 1 swarf collecting vessel, fitted
- + 1 guide rail adapter
- + 2 x ProCORE 18 V 8.0 Ah AS battery pack
- + 1 plastic tool case (L-BOXX 238)

Technical data

TECHNICAL DATA



VIBRATION AND SOUND EMISSION VALUES

		VALUES	
Battery voltage	18 V	Sound pressure level LpA Uncertainty of measured value KpA	99,2 dB 3 dB
Battery capacity	8 Ah		
Battery compatibility	Li-ion / ProCORE Li-ion	Sound power level LWA Uncertainty of measured value KWA	107,2 dB 3 dB
Battery interface	18 V AMPShare	Sound peak value	122,7 dB
Speed, no load	1 300 - 2 800 rpm	LpCpeak Uncertainty of measured value KpCpeak	3 dB
Max. cutting depth	57 mm	Vibration value 1 α hv 3-	1,1 m/s ²
Max. saw blade thickness	2 mm	Way Vibration value 2 αhv 3-way	1,1 m/s ²
Saw blade Ø	150 mm	Uncertainty of measured	1,5 m/s²
Mounting hole Ø	20 mm	value K $lpha$	
Width	179 mm		
Height	249 mm		
Length	287 mm		
Steel up to 400 N/mm²	24 mm		
Steel up to 800 N/mm²	4 mm		
Non-ferrous metals up to	40 mm		

Application examples

Dimensions of base plate

Weight without storage

256 x 131 mm

3.05 kg

250 N/mm²

battery

















