



# BLK 5.0 E

## Nibbler up to 5 mm

Powerful nibbler for heavy dismantling and cutting applications.

Product number: 7 232 47 61 00 0

### Details

- + Suited to cuts over 90° edges, for example on guard rails or during tank decommissioning.
- + Incredible power delivered by the 1700 W motor while also offering outstanding ergonomics and optimum power-to-weight ratio.
- + Extensive user protection: restart protection, blocking protection, overload protection, soft start.
- + Cutting direction: 4 x 90°, can be adjusted without the need for tools.
- + Variable stroke.
- + Tool-free quick change system for die and punch.
- + Ergonomic handle suited to guiding in all directions.
- + Chip protection mesh in fan area.
- + Wide range of accessories.

### Price includes

- + 1 die 5, steel (31309107000) fitted
- + 1 additional handle fitted
- + 1 punch 5/P5 steel (31309141000) fitted
- + 1 plastic tool case (L-BOXX 238)

### Product feature

- + Cutting direction
- + Adjustable stroke
- + QuickIN
- + Additional handle

### Application

Curve cuts



Interior cut-outs



Profile sections



Notches





+ suitable  
 ++ well suitable

## Technical data

### TECHNICAL DATA

Input	1,700 W
Output	1,000 W
Strokes	820 rpm
Cutting speed	1,5 m/min
Steel up to 400 N/mm <sup>2</sup>	5 mm
Steel up to 600 N/mm <sup>2</sup>	3.3 mm
Steel up to 800 N/mm <sup>2</sup>	2.5 mm
Non-ferrous metals up to 250 N/mm <sup>2</sup>	7 mm
Cutting width	8 mm
Immersion Ø with die	43 mm
Rad. of smallest curve (inside/outside)	90 / mm
Cable with plug	4 m
Weight according to EPTA	3.80 kg
Weight according to EPTA	3.80 kg

### VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Uncertainty of measured value KpA	95,8 dB 3 dB
Sound power level LWA Uncertainty of measured value KWA	103,8 dB 3 dB
Sound peak value LpCpeak Uncertainty of measured value KpCpeak	112,4 dB 3 dB
Vibration value 1 αhv 3-way Uncertainty of measured value Kα	12,4 m/s <sup>2</sup> 1,5 m/s <sup>2</sup>

## Application examples

