



BLK 1.6 E

Nibbler up to 1.6 mm

Universal nibbler for sheets, profiles, trapezoid and corrugated sheet metals.

Product number: 7 232 38 60 00 0

Details

- + Almost indestructible. Ideal for flexible and universal use with sheet thickness up to 1.6 mm..
- + Optimum ergonomics with a handle up to 20% slimmer because of its extremely thin drive head.
- Cutting direction setting can be changed in 45° steps up to 360° using tool-free pivoting cutting head.
- + QuickIN clamping system.
- + High cutting speed.

- + Rotating punch for a service life which is now up to 30 % longer.
- + Low operating costs due to long tool life of punch and die.
- + Motor with outstanding performance and stability.
- + Chip protection mesh on vent slots.
- + 5 metre cable.
- + Stainless steel up to 0.7 mm.
- + Retrofittable trapezoid profile set up to 160 mm deep channels.

Price includes

- + 1 die (30109141003) fitted
- + 1 socket head wrench 6 mm
- + 1 punch (63602048004) fitted

Product feature

- + Rotating round punch
- + QuickIN

- + Cutting direction
- + Adjustable stroke

Application

Curve cuts

Coil sections

Interior cut-outs

++
++



Profile sections

Notches

++

+ suitable

Κα

++ well suitable

Technical data

Weight according to

EPTA

TECHNICAL DATA

VIBRATION AND SOUND EMISSION VALUES

350 W Input 210 W Output Strokes 800 - 1,500 rpm Cutting speed 1.9 m/min Steel up to 400 N/mm² 1.6 mm 1 mm Steel up to 600 N/mm² 0.7 mm Steel up to 800 N/mm² 2.5 mm Non-ferrous metals up to 250 N/mm² 5 mm Cutting width Immersion Ø with die 22 mm Rad. of smallest curve 30 / 35 mm (inside/outside) 5 m Cable with plug

1.80 kg

82 dB Sound pressure level LpA Uncertainty of measured value 3 dB KpA 93 dB Sound power level LWA Uncertainty of measured value 3 dB KWA Sound peak value 93 dB LpCpeak Uncertainty of measured value 3 dB **KpCpeak** Vibration value 1 α hv 3-8,8 m/s² Uncertainty of measured value 1,5 m/s²



Application examples

