



HSS Dura 25 core bit with 3/4 in Weldon holder

TiN surface coating for outstanding service lives and the best glide properties.

Metric dimensions, cutting depth 25 mm.

Product number: 6 31 34 150 07 5

Technical data

TECHNICAL DATA

Cutting depth

25 mm

Bore Ø

15 mm

Suitable for the following tools

Universal

- > KBU 35 Q
- > KBU 35 MQ
- > KBU 35-2 Q
- > KBU 35 QW
- > KBU 35 MQW
- > KBU 35-2 QW
- > KBU 35 PQW
- > KBU 35 PQ
- > KBM 50 U
- > KBM 50 Q
- > KBM 65 U
- > KBU 35 QW Fabricator
M12 Tapping-Set 3/4 in
Weldon
- > KBM 50 UQW
- > KBM 65 UQW
- > KBU 35 QW Structural
Steel-Set 3/4 in Weldon
- > AKBU 35 PMQ AS
- > AKBU 35 PMQW AS
- > AKBU 35 PMQW 18 V AS
set 2x 8 Ah
- > AKBU 35 PMQW 18 V AS
- Set 1x 12 Ah
- > AKBU 35 PMQW AS
CONSTRUCTION SITE
set 3/4 in Weldon / HSS
NOVA 50
- > AKBU 35 PMQW 18 V AS
CONSTRUCTION SITE 1x
12 Ah set 3/4 in Weldon /
HSS NOVA 50
- > AKBU 35 PMQW 18 V AS
CONSTRUCTION SITE 2x
8 Ah set 3/4 in Weldon /
HSS NOVA 50



Endurance

- > KBE 50-2
- > KBE 32
- > KBE 32 QW
- > KBE 36 MAGSPEED
- > KBE 36 QW MAGSPEED
- > KBE 36 QW MAGSPEED Fabrication Set

Automatic

- > KBM 50 auto
- > KBM 50 auto QW