



## ASCM 18-4 QM AS Metal Advanced Set

Cordless drill/driver in user set.

The all-rounder ASCM 18-4 QM AS with 8-piece bit set, QuickIN bit holder 1/4", QuickIN tapping collets 4.5 mm and 6 mm, HSS cobalt 5% twist drill set 6-piece and HSS tap set 7-piece.

Product number: 7 116 15 64 00 0

#### Details

- + 4-speed solid metal gearbox. With speeds of up to 4000 rpm for optimum cutting speeds in metal for any holes between 1.5 and 80 mm.
- Enjoy the greatest versatility with the FEIN
   QuickIN system for multi-functional use on all
   drilling, core drilling, tapping, countersinking and
   screwdriving jobs.
- + The QuickIN headers can be changed in a matter of seconds and without the need for tools when users switch between applications in metal and timber and have just one tool.
- + Very safe working. Kickback monitoring stops the tool.
- + Extendible extra handle for more control.
- + The brushless, powerful FEIN PowerDrive motor is up to 30% more efficient and makes a longer service life possible.
- + High torques up to a maximum of 130 Nm.
- QuickIN solid metal drill chuck (120 Nm) with carbide-tipped clamping jaws and high clamping forces.
- + Electronic torque setting (15+1).
- + Intuitive operating panel with LED which can be dimmed for perfectly illuminating the workplace to suit the material.
- + Bit and belt holder on the side for ergonomic and flexible handling.

- + Bit set 8-piece. Bit holder and 7 bits (PZ2, PZ3, T15, T20, T25, T30, T40, 60-1/4).
- + HSS cobalt 5% twist drill set 6-piece (2 mm, 3 mm, 4 mm, 5 mm, 6 mm, 8 mm).
- + HSS tap set 7-piece (M3, M4, M5, M6, M8, M10, M12).
- + QuickIN bit holder, QuickIN tapping collets 4.5 mm and 6 mm.
- + Fixes 10 x 400 mm screws without pre-drilling.
- + AMPShare interface makes 1400 screw connections (5 x 40 mm in timber) possible per battery charge (ProCORE 4 Ah).
- + Extensive user protection features include restart protection, electronic overload protection and brake.
- + The innovative adjustment function enables screw connections to be made in timber at a reduced speed for perfect results.
- + Compatible with Bosch Professional 18 V batteries (available since 2008) and AMPShare batteries.
- → Maximum work progress with AMPShare 18V ProCORE batteries: COOLPACK 2.0 technology delivers a 135% longer battery life. State-of-theart cell technology and intelligent battery management deliver 87% more power than with conventional batteries. "Electronic Cell



Protection" (ECP) protects the battery from overload, overheating and total discharge.

Ideally equipped for every job. Mobile working with the L-BOXX system.

#### Price includes

- + 1 ASCM 18-4 QM AS (incl. handle, belt clip, bit holder)
- + 1 QuickIN bit holder
- + 1 QuickIN tapping collet 6 mm
- + 1 HSS tap set 7-piece

- + 1 8-piece bit set
- + 1 QuickIN tapping collet 4.5 mm
- + 1 HSS cobalt 5% twist drill set 6 pieces
- + 1 tool case (L-Boxx 136)

#### Product feature

- + Removable drill chuck
- + 4-speed gearbox
- + Dimmable LFD

- + Electronic torque shut-off
- + QuickIN accessory interface
- + Drilling and over screw function

#### Technical data

#### TECHNICAL DATA

# VIBRATION AND SOUND EMISSION VALUES

Battery voltage	18 V
Battery compatibility	Li-ion / ProCORE Li-ion
Battery interface	18 V AMPShare
Motor	brushless
Gearbox	4-speed
Accessory interface	QuickIN
Speed, no load	430 / 850 / 2 000 / 4 000 rpm
Max. torque (hard/soft)	130 (70 / 50) Nm

Sound pressure level LpA
Uncertainty of measured value
KpA

Sound power level LWA
Uncertainty of measured value

Sound power level LWA Uncertainty of measured value KWA

Sound peak value LpCpeak Uncertainty of measured value KpCpeak

Vibration value 1  $\alpha$ hv 3-way Vibration value 2  $\alpha$ hv 3-way

Uncertainty of measured

75,9 dB 5 dB

83,9 dB 5 dB

90,6 dB

5 dB

ah,D 0,9 m/s<sup>2</sup>

ah 0,6 m/s²

 $1,5 \text{ m/s}^2$ 



Torque levels

15 + 1

value  $K\alpha$ 

Drill chuck clamping width

1.5 - 13 mm

Fastening

10 x 400 mm

Drill Ø steel twist drill

13 mm

Drilling diameter in steel, core drill bit

30 mm

Drilling diameter in steel, hole saws

80 mm

Capacity in wood Ø

60 mm

**Tapping** 

M 14

Weight without storage battery

1.30 kg

### Application examples





Kompatibel mit AMPShare-/ Bosch Professional 18 V Akkus. | Compatible with AMPShare/Bosch

Professional 18 V batteries. | Compatible avec les batteries 18 V AMPShare/Bosch Professional. | Compatible con baterías AMPShare/Bosch Professional de 18 V. | Compatibile con le batterie AMPShare / Bosch Professional da 18 V.



















