



ABS 18 Q AS Set 5 Ah

2-speed cordless drill/driver

With brushless motor and QuickIN interface. Perfectly suited to drilling up to 13 mm and tapping up to M10.

Product number: 7 113 24 62 00 0

Details

- + Two-speed solid metal gearbox perfectly suited to drilling up to 13 mm and tapping up to M10 in metal.
- + Enjoy the greatest versatility with the FEIN QuickIN system. Work at speed in metal and timber with just one tool.
- QuickIN solid metal drill chuck (120 Nm) with carbide-tipped clamping jaws and high clamping forces.
- + Brushless FEIN PowerDrive motor with 30 % higher efficiency and long service life.
- + Mechanical torque setting.
- + Compact design.
- → The AMPShare interface makes almost 50% more screw connections (approx. 1600 screw connections, diameter of 5 x 40 mm in timber)

- possible per battery charge with the same level of FEIN quality. (GBA 18 V 5 Ah).
- + Bit and belt holder on the side for ergonomic and flexible handling.
- + Compatible with Bosch Professional 18 V batteries (available since 2008) and AMPShare batteries.
- → Maximum work progress with AMPShare 18V ProCORE batteries: COOLPACK 2.0 technology delivers a 135% longer battery life. State-of-theart cell technology and intelligent battery management deliver 87% more power than with conventional batteries. "Electronic Cell Protection" (ECP) protects the battery from overload, overheating and total discharge.
- + Ideally equipped for every form of use. Mobile working with the L-BOXX system.

Price includes

- + 1 QuickIN drill chuck (120 Nm)
- + 1 magnetic bit storage
- + 2 Li-lon storage battery GBA 18V 5.0 Ah AS
- + 1 belt clip
- + 1 tool case (L-Boxx 136)
- + 1 rapid charger GAL 1880 CV AS

Product feature

+ Removable drill chuck

+ QuickIN accessory interface

Technical data

TECHNICAL DATA



VIBRATION AND SOUND EMISSION VALUES

Battery voltage	18 V	Sound pressure level LpA Uncertainty of measured value	74,3 dB 5 dB
Battery capacity	5 Ah	КрА	
Battery compatibility	Li-ion / ProCORE Li-ion	Sound power level LWA Uncertainty of measured value KWA	82,3 dB 5 dB
Battery interface	18 V AMPShare	Sound peak value	88,1 dB
Motor	brushless	LpCpeak Uncertainty of measured value KpCpeak	5 dB
Gearbox	2-speed		
Accessory interface	QuickIN	Vibration value 1 α hv 3-way Vibration value 2 α hv 3-way	ah,D 1,1 m/s² ah 1,2 m/s²
Speed, no load	450 / 2,000 rpm	Uncertainty of measured	1,5 m/s²
Max. torque (hard/soft)	60 / 38 Nm	value K α	
Torque levels	22 + 1		
Drill chuck clamping width	1.5 - 13 mm		

Application examples

Fastening

Tapping

battery

Capacity in steel Ø

Capacity in wood Ø

Weight without storage

8 x 300 mm

13 mm

50 mm

M 10

1.40 kg





Powered by BOSCH

Kompatibel mit AMPShare-/ Bosch Professional 18 V Akkus. | Compatible with AMPShare/Bosch

Professional 18 V batteries. | Compatible avec les batteries 18 V AMPShare/Bosch Professional. | Compatible con baterías AMPShare/Bosch Professional de 18 V. | Compatibile con le batterie AMPShare / Bosch Professional da 18 V.





