



ASCD 18-300 W2 AS Impact-tapping-top Set

User set contains a cordless impact wrench/driver

Cordless impact wrench/driver with 1/2" square head tool mounting. The set includes 1/2" VARIO adapter, 5-part FEIN VARIO tapper set for through holes and circlip along with a battery (GBA 18 V 5.0 Ah AS) and rapid charger (GAL 1880 CV AS).

Product number: 7 115 10 64 00 0



Details

- + For extreme precision work: The ASCD 18-300 W2 AS with electronic torque setting (6 levels) prevents screw heads from shearing off.
- Impact wrench/driver-compatible VARIO adapter turns the impact wrench/driver into a tapper, thereby adding a whole new tool to the range of applications.
- + The 5-part FEIN VARIO tapper set covers sizes M8, M10, M12, M14, M16.
- → VARIO tapper for through holes. Long service life, thanks to high material strength (64 HRC), special cutting geometries suited to impact wrench/drivers and a TiAlN (titanium-aluminium-nitride) coating. The bits experience low levels of wear and friction as well as being heat-resistant to 800 °C. Thanks to the high speeds and number of blows, they can therefore be used in steel up to 900 N/mm².

- → Brushless FEIN PowerDrive motor with 30 % higher efficiency and long service life.
- + 1/2" square for holding sockets.
- + Metric screws up to M18 (8.8).
- + Compatible with Bosch Professional 18 V batteries (available since 2008) and AMPShare batteries.
- Maximum work progress with AMPShare 18V storage batteries: COOLPACK 1.0 technology ensures a longer storage battery life compared with batteries without COOLPACK technology and therefore makes longer operating periods possible. ECP protects the storage battery against overload, overheating and total discharge.
- + Ideally equipped for every form of use. Mobile working with the L-BOXX system.

Price includes

- + 1 x ASCD 18-300 W2 AS (including belt clip, bit holder)
- + 1 rapid charger GAL 1880 CV AS
- + 1 x 5-part VARIO tapper set (M8, M10, M12, M14, M16)
- + 1 tool case (L-Boxx 136)

- + 1 BATTERY PACK GBA 18 V 5.0 AH AS
- + 1 X 1/2" VARIO adapter
- + 1 x locking spring

Technical data

Motor

TECHNICAL DATA

VIBRATION AND SOUND EMISSION VALUES

Battery voltage

Battery compatibility

Li-ion / ProCORE Li-ion

Battery interface

18 V AMPShare

brushless

Sound pressure level LpA Uncertainty of measured value KpA

Sound power level LWA Uncertainty of measured value KWA

99,2 dB 3 dB

107,2 dB 3 dB



Speed, no load

Impacts

Max. torque

Torque levels

Tool Holder

Max. metric screw

Wood screw Ø

Weight without storage battery

0 - 1700 rpm

0 - 3400 rpm

290 Nm

6

1/2" Outer square

M18 (8.8)

8 x 300 mm

1.20 kg

Sound peak value
LpCpeak
Uncertainty of measured y

Uncertainty of measured value KpCpeak

Vibration value 1 α hv 3-way

Uncertainty of measured value $K\alpha$

121,5 dB

3 dB

 α h 15,0 m/s²

1,5 m/s²

Application examples



⊜ BOSCH

Kompatibel mit AMPShare-/ Bosch Professional 18 V Akkus. | Compatible with AMPShare/Bosch

















With AMP-Share/Bosch Professional 18 V batteries. | Compatible avec les batteries 18 V AMPShare/Bosch Professional. | Compatible con baterias AMPShare/Bosch Professional de 18 V. | Compatible con le batterie AMPShare / Bosch Professional da 18 V.