



## ABH 18-26 AS

### Cordless rotary hammer drill

With SDS plus and an impact energy of 2.6 joules for drilling up to 26 mm in concrete.

Product number: 7 140 03 62 00 0

## Details

- + The powerful, brushless motor delivers 2.6 joules of impact energy and ensures rapid drilling progress as well as high chisel grinding capacity.
- + Kickback monitoring with intelligent rapid shutdown should the hammer drill kick back suddenly for optimum user protection.
- + Electronic Precision Control (EPC) slowly ramps up the working speed for perfect handling and control when working with sensitive materials and challenging surfaces.
- + Simple and precise speed control using the throttle.
- + Fatigue-free working thanks to compact design and few vibrations.
- + Change the chisel position (Vario-Lock) – lock the chisel in 36 positions for the optimum working position every time.
- + Bright working area thanks to integrated LED light.
- + Clamps or hooks the bit if the drive to the drill spindle is interrupted.
- + Compatible with Bosch Professional 18 V batteries (available since 2008) and AMPShare batteries.
- + Maximum work progress with AMPShare 18V ProCORE batteries: COOLPACK 2.0 technology delivers a 135% longer battery life. State-of-the-art cell technology and intelligent battery management deliver 87% more power than with conventional batteries. “Electronic Cell Protection” (ECP) protects the battery from overload, overheating and total discharge.
- + ProCORE Li-Ion battery with high-power cells, charge status indicator and “Electronic Cell Protection” (ECP). ECP protects against overload, overheating and total discharge.
- + Ideally equipped for every form of use. Mobile working with the L-BOXX system.

## Price includes

- + 1 handle
- + 1 x tool cloth
- + 2 Li-Ion storage battery GBA 18V 5.0 Ah AS
- + 1 depth stop
- + 1 tool case (L-Boxx 136)
- + 1 rapid charger GAL 1880 CV AS

## Technical data

### TECHNICAL DATA



## VIBRATION AND SOUND EMISSION VALUES

|                                |                         |                                                                                |                                                                             |
|--------------------------------|-------------------------|--------------------------------------------------------------------------------|-----------------------------------------------------------------------------|
| Battery voltage                | 18 V                    | Sound pressure level LpA<br>Uncertainty of measured value<br>KpA               | 88 dB<br>3 dB                                                               |
| Battery capacity               | 5 Ah                    |                                                                                |                                                                             |
| Battery compatibility          | Li-ion / ProCORE Li-ion | Sound power level LWA<br>Uncertainty of measured value<br>KWA                  | 99 dB<br>3 dB                                                               |
| Battery interface              | 18 V AMPShare           |                                                                                |                                                                             |
| Motor                          | brushless               | Vibration value 1 $\alpha_{hv}$ 3-way<br>Vibration value 2 $\alpha_{hv}$ 3-way | $\alpha_{h,D}$ 15,2 m/s <sup>2</sup><br>$\alpha_{h,D}$ 9,9 m/s <sup>2</sup> |
| Speed, no load                 | 0 - 980 rpm             |                                                                                |                                                                             |
| Impacts                        | 0 - 4,350 rpm           | Uncertainty of measured value<br>K $\alpha$                                    | 1,5 m/s <sup>2</sup>                                                        |
| Impact energy                  | 2.6 J                   |                                                                                |                                                                             |
| Tool Holder                    | SDS-plus                |                                                                                |                                                                             |
| Hole diameter, concrete        | 26 mm                   |                                                                                |                                                                             |
| Hole diameter, masonry         | 68 mm                   |                                                                                |                                                                             |
| Capacity in steel Ø            | 13 mm                   |                                                                                |                                                                             |
| Capacity in wood Ø             | 30 mm                   |                                                                                |                                                                             |
| Weight without storage battery | 3.20 kg                 |                                                                                |                                                                             |

## Application examples



# FEIN



Powered by



**BOSCH**

**Kompatibel mit  
AMPSHARE- / Bosch  
Professional 18 V  
Akkus. | Compatible  
with AMPSHARE/Bosch**

Professional 18 V batteries. | Compatible avec  
les batteries 18 V AMPSHARE/Bosch Professional. |  
Compatible con baterías AMPSHARE/Bosch  
Professional de 18 V. | Compatibile con le batterie  
AMPSHARE / Bosch Professional da 18 V.

