



FEIN



GSZ 11-320 PERL

Straight grinder 32 500/min

Ergonomic, extremely powerful die grinder with high plunge depth for heavy-duty grinding and deburring in difficult-to-reach spots.

Product number: 7 223 22 60 00 0

Details

- + Long narrow neck allows tool to plunge a long way into workpieces (e.g. grinding inside pipes).
- + User protection features include blockage monitoring, restart protection, soft start and electronic overload protection.
- + Innovative collets with all-round flange to protect the workpiece and prevent the wrench sliding off during tool changes.
- + POWERtronic tachoelectronics for enormous power, power reserve and exceptional speed stability under load.
- + Removable rubber collar bearing cover.
- + Motor and electronics protected against metal dust.
- + Variable speed allows different tools to be used.

Price includes

- + 1 collet Ø 8 mm
- + Jaw spanner SW17
- + Jaw spanner SW13

Product feature

- + Long neck

Application



FEIN

Cutting	++
Roughing-down	++
Grinding	++
Deburring	+
Brushing	+

+ suitable
++ well suitable

Technical data

TECHNICAL DATA

Input	1,010 W
Output	620 W
Speed, no load	9,500 - 32,500 rpm
Grinding wheel for max. Ø	45 mm
Collet for max. Ø	8 mm
Collar Ø	43 mm
Max. cutter diameter	12 mm
Cable with plug	4 m
Weight according to EPTA	2.10 kg

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Uncertainty of measured value KpA	85 dB 3 dB
Sound power level LWA Uncertainty of measured value KWA	96 dB 3 dB
Sound peak value LpCpeak Uncertainty of measured value KpCpeak	98 dB 3 dB
Vibration value 1 α_{hv} 3-way Uncertainty of measured value K α	9,7 m/s ² 1,5 m/s ²

Application examples

