

+ Jaw spanner SW13



GSZ 8-280 P

Straight grinder 28 000/min

Ergonomic, powerful die grinder for grinding and deburring in difficult-to-reach spots; also suitable for semi-stationary use.

Product number: 7 223 16 60 00 0

Details

- Compact design for use in especially tight spaces, collar diameter of 43 mm for semistationary use as milling motor (e.g. as profile miller).
- User protection features include blockage monitoring, restart protection, soft start and electronic overload protection.
- Innovative collets with all-round flange to protect the workpiece and prevent the wrench sliding off during tool changes.
- POWERtronic tachoelectronics for enormous power, power reserve and exceptional speed stability under load.
- Motor and electronics protected against metal dust.

Price includes

- + 1 collet Ø 6 mm
- + Jaw spanner SW17

Application



+ suitable

+ + well suitable

Cutting

Grinding

Technical data TECHNICAL DATA

VIBRATION AND SOUND EMISSION VALUES

Input	750 W	Sound pressure level LpA Uncertainty of measured value KpA	84 dB 3 dB
Output	400 W		
Speed, no load	28,000 rpm	Sound power level LWA Uncertainty of measured value KWA	95 dB 3 dB
Grinding wheel for max. Ø	45 mm	Sound peak value LpCpeak	97 dB
Collet for max. Ø	8 mm	Uncertainty of measured value KpCpeak	3 dB
Collar Ø	43 mm	Vibration value 1 α hv 3-	4,7 m/s²
Max. cutter diameter	12 mm	Way Uncertainty of measured value K a	1,5 m/s²
Cable with plug	4 m		
Weight according to EPTA	1.40 kg		

Application examples





