



MOtlx 6-25

Oscillating multi-tool - compressed air

The powerful pneumatic oscillator for cargo.

Product number: 7 536 03 00 01 0

Details

- + Available with a comprehensive range of accessories for professional use in many industry sectors.
- → Powerful oscillating motion with amplitude of 2 x
 1.6 degrees for maximum work progress.

2 x 1,6°

- + Ideal for removing bonded panes from lorries, buses and rail vehicles.
- + Small size.
- + Supplied with inlet and outlet air hose.
- + No air leaks, no oil misting in working area.
- + Hexagonal tool mounting.

Price includes

+ 2 keys

Amplitude

+ 1 plastic carrying case

Technical data

TECHNICAL DATA

VIBRATION AND SOUND EMISSION VALUES

| Operating pressure | 6.3 bar | Sound pressure level LpA Uncertainty of measured value KpA | 82 dB 3 dB |
|--------------------|--------------------------------------|--|---------------|
| Air consumption | 0.6 m³/min | | |
| Oscillations | 20,000 rpm | Sound power level LWA Uncertainty of measured value KWA | 93 dB 3 dB |
| Hose size Ø | 8 mm | Uppertainty of managerad | 3 dB |
| Tool Holder | Hexagon | Uncertainty of measured value KpCpeak | 3 06 |
| Tool change | Manual with screw, hexagon socket | | |



Weight according to EPTA

0.90 kg