



# MULTIMASTER MM 700 1.7 Q Basic

## Oscillating multi-tool – MM 700

Our best oscillating MultiMaster for the automotive sector.

Product number: 7 229 69 63 00 0

### Details

- + Designed for cutting out windows and work on the car body.
- + Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- + QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.
- + Hexagonal tool holder for optimum torque transfer.
- + 450 W FEIN high-power motor: high-power motor with a high copper content, which is suited to continuous use and overload for maximum cutting speed and the most rapid work progress.
- + Tacho generator: constant speeds even under load and infinitely variable electronic speed control.
- + Metal gearbox: ability to withstand high loading and outstanding service life because all the gearbox parts are made from metal.
- + Industrial cable: large working radius thanks to finely stranded 5 metre rubber cable of industrial quality.
- + Ideally equipped for every job. Mobile working with the L-BOXX system.

### Price includes

- + 1 protective cover for tool changes
- + 1 sharpening stone (63719010014)
- + 1 tool case (L-Boxx 136)

### Technical data

#### TECHNICAL DATA

|              |                     |
|--------------|---------------------|
| Input        | 450 W               |
| Output       | 250 W               |
| Oscillations | 10,000 - 19,500 rpm |

#### VIBRATION AND SOUND EMISSION VALUES

|                                                                  |               |
|------------------------------------------------------------------|---------------|
| Sound pressure level LpA<br>Uncertainty of measured value<br>KpA | 82 dB<br>3 dB |
| Sound power level LWA<br>Uncertainty of measured value           | 93 dB<br>3 dB |



# FEIN

|                          |          |                                          |       |
|--------------------------|----------|------------------------------------------|-------|
| Tool Holder              | 12-sided | KWA                                      |       |
| Tool change              | QuickIN  | Sound peak value<br>LpCpeak              | 96 dB |
| Amplitude                | 2 x 1,7° | Uncertainty of measured value<br>KpCpeak | 3 dB  |
| Cable with plug          | 5 m      |                                          |       |
| Weight according to EPTA | 1.45 kg  |                                          |       |

## Application examples

