



# MULTIMASTER MM 700 1.7 Q Autoglas

## Oscillating multi-tool – MM 700

Our best oscillating MultiMaster for the automotive sector including an extensive set of accessories extensive for cutting out windows and work on the car body.

Product number: 7 229 70 65 00 0

### Details

- + Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- + QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.
- + Hexagonal tool holder for optimum torque transfer.
- + 450 W FEIN high-power motor: high-power motor with a high copper content, which is suited to continuous use and overload for maximum cutting speed and the most rapid work progress.
- + Tacho generator: constant speeds even under load and infinitely variable electronic speed control.
- + Metal gearbox: ability to withstand high loading and outstanding service life because all the gearbox parts are made from metal.
- + Industrial cable: large working radius thanks to finely stranded 5 metre rubber cable of industrial quality.
- + Ideally equipped for every job. Mobile working with the L-BOXX system.

### Price includes

- + 3 L-shaped cutter blades, toothed (form 207)
- + 1 L-shaped cutter blade, toothed (form 209)
- + 2 U-shaped cutter blades, reinforced design, toothed (form 212)
- + 1 Straight cutter blade, Z-bend, toothed (form 081)
- + 1 sharpening stone (63719010014)
- + 2 L-shaped cutter blades, toothed (form 208)
- + 1 each U-shaped cutter blade, reinforced design (forms 157 and 111)
- + 1 Straight cutter blade, Z-bend, with adjustable roller stop (form 143)
- + 1 protective cover for tool changes
- + 1 tool case (L-BOXX 136)

## Technical data

### TECHNICAL DATA

|                          |          |
|--------------------------|----------|
| Input                    | 450 W    |
| Output                   | 250 W    |
| Oscillations             | - rpm    |
| Tool Holder              | 12-sided |
| Tool change              | QuickIN  |
| Amplitude                | 2 x 1,7° |
| Cable with plug          | 5 m      |
| Weight according to EPTA | 1.65 kg  |

### VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA  
Uncertainty of measured value  
KpA

87,4 dB  
3 dB

Sound power level LWA  
Uncertainty of measured value  
KWA

95,4 dB  
3 dB

Sound peak value

100,3 dB

LpCpeak  
Uncertainty of measured value  
KpCpeak

3 dB

## Application examples

