



MULTIMASTER MM 700 1.7 Q Grouting Renewal

Oscillating multi-tool – MM 700

Our best MultiTool specially for grouting renewal with durable 12-star receptacle and 7 blades for cutting out elastic joints.

Product number: 7 229 70 66 00 0

Details

- + Precision – MultiTools get into hard-to-reach places. Thanks to vibration damping, they work quietly and precisely.
- + Versatility – blade lengths up to 98 mm allow even very deep joints to be cut. The diamond-coated cleaning blade cleans mortar flanks before you fill them in again.
- + Safety and simplicity – MultiTools work precisely and safely in the joint. Blades don't break and the power tool is protected against overload and overheating. Misuse is almost impossible.
- + QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.
- + 12-sided holder for optimum torque transfer.
- + 450 W FEIN high-power motor: high-power motor with a high copper content, which is suited to continuous use and overload for maximum cutting speed and the most rapid work progress.
- + Tacho generator: constant speeds even under load and infinitely variable electronic speed control.
- + Metal gearbox: ability to withstand high loading and outstanding service life because all the gearbox parts are made from metal.
- + Industrial cable: large working radius thanks to finely stranded 5 metre rubber cable of industrial quality.
- + Ideally equipped for every form of use. Mobile working with the L-BOXX system.

Price includes

- + 5 Cutter blades, straight (form 117) 6 390 31 17 01 5
- + 1 Cutter blade, mushroom shaped 6 390 31 28 01 2
- + 1 protective cover for tool changes
- + 1 plastic tool case (L-BOXX 238)
- + 1 Cutter blade, straight, long (form 116) 6 390 31 16 01 1
- + 1 handle
- + 1 sharpening stone (63719010014)

Technical data

TECHNICAL DATA



VIBRATION AND SOUND EMISSION VALUES

Input	450 W	Sound pressure level LpA Uncertainty of measured value KpA	82 dB 3 dB
Output	250 W		
Oscillations	10,000 - 19,500 rpm	Sound power level LWA Uncertainty of measured value KWA	93 dB 3 dB
Tool Holder	12-sided		
Tool change	QuickIN	Sound peak value LpCpeak Uncertainty of measured value KpCpeak	96 dB 3 dB
Amplitude	2 x 1,7°		
Cable with plug	5 m	Uncertainty of measured value K α	1,5 m/s ²
Weight according to EPTA	1.65 kg		

Application examples

