



ASAS 18-21 K AS Set 2 x 4 Ah

Compact cordless sabre saw

Compact, low-vibration sabre saw for mobile and universal use for cutting various materials, particularly well suited to hard-to-reach places. Including battery starter set of 2 x 4 Ah ProCORE batteries and rapid charger.

Product number: 7 133 01 62 00 0

Details

- + Rapid work progress when sawing thanks to the powerful DC motor.
- + The right solution for virtually all materials and applications: the SDS system for rapid, tool-free saw blade changes.
- + Optimised size and reduced vibrations for low-fatigue working.
- + LED light illuminates the working area.
- + Speed can be variably controlled via throttle.
- + Ergonomic design including soft grip.
- + Compatible with all 18 V AMPShare ProCORE batteries and chargers for even more power and flexibility. Also suitable for 18 V Bosch Professional cordless devices.
- + Maximum work progress with AMPShare 18V ProCORE batteries: COOLPACK 2.0 technology delivers a 135% longer battery life. State-of-the-art cell technology and intelligent battery management deliver 87% more power than with conventional batteries. "Electronic Cell Protection" (ECP) protects the battery from overload, overheating and total discharge.
- + Ideally equipped for every form of use. Mobile working with the L-BOXX system.

Price includes

- + 1 x BIM 130 T18 MS sabre saw blade
- + 1 x BIM 130 T5/8 WP sabre saw blade
- + 1 rapid charger GAL 1880 CV AS
- + 2 x ProCORE 18 V 4.0 Ah AS battery pack
- + 1 tool case (L-Boxx 136)

Technical data

TECHNICAL DATA

VIBRATION AND SOUND EMISSION VALUES



FEIN

Battery voltage	18 V	Sound pressure level LpA Uncertainty of measured value KpA	82 dB 5 dB
Battery compatibility	Li-ion / ProCORE Li-ion	Sound power level LWA Uncertainty of measured value KWA	93 dB 5 dB
Battery interface	18 V AMPShare	Uncertainty of measured value KpCpeak Vibration value 1 α_{hv} 3-way	5 dB 8 m/s ²
Strokes wood	0 - 3 050 rpm 200 mm	Uncertainty of measured value K α	1,5 m/s ²
Metal profiles and metal pipes	100 mm		
Stroke of blade	21 mm		
Width	78 mm		
Height	177 mm		
Length	367 mm		
Weight without storage battery	2.00 kg		

Application examples



