



# BLK 1.6 LE

## Nibbler up to 1.6 mm

Compact nibbler for deep-channel trapezoidal sheet metals in roof and façade construction.

Product number: 7 232 39 60 00 0

### Details

- + The specialist when it comes to zero compromise work on trapezoidal sheet metals with deep channels of up to 160 mm.
- + Optimum ergonomics with a handle up to 20% slimmer because of its extremely thin drive head.
- + Cutting direction setting can be changed in 45° steps up to 360° using tool-free pivoting cutting head.
- + QuickIN clamping system.
- + High cutting speed.
- + Motor with outstanding performance and stability.
- + Chip protection mesh on vent slots.
- + 5 metre cable.
- + Stainless steel up to 0.7 mm.

### Price includes

- + 1 die for trapezoid sheet metal (31309122005) fitted
- + 1 wearing plate fitted
- + 1 punch (63602049008) fitted

### Product feature

- + Cutting direction
- + Adjustable stroke
- + QuickIN

### Application

Curve cuts



Interior cut-outs



Profile sections



Notches





+ suitable  
 ++ well suitable

## Technical data

### TECHNICAL DATA

Input	350 W
Output	210 W
Strokes	800 - 1,500 rpm
Cutting speed	2.7 m/min
Steel up to 400 N/mm <sup>2</sup>	1.6 mm
Steel up to 600 N/mm <sup>2</sup>	1 mm
Steel up to 800 N/mm <sup>2</sup>	0.7 mm
Non-ferrous metals up to 250 N/mm <sup>2</sup>	2.5 mm
Cutting width	5 mm
Immersion Ø with die	24 mm
Rad. of smallest curve (inside/outside)	65 / 70 mm
Cable with plug	5 m
Weight according to EPTA	1.90 kg
Weight according to EPTA	1.90 kg

### VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Uncertainty of measured value KpA	82 dB 3 dB
Sound power level LWA Uncertainty of measured value KWA	93 dB 3 dB
Sound peak value LpCpeak Uncertainty of measured value KpCpeak	93 dB 3 dB
Vibration value 1 $\alpha_{hv}$ 3-way Uncertainty of measured value K $\alpha$	8,8 m/s <sup>2</sup> 1,5 m/s <sup>2</sup>

## Application examples

