



BLS 1.6 E set

Sheet Shear, up to 1,6 mm

Easy-to-use, curve-compatible sheet metal shears for cutting and trimming thin sheets. Includes second plunger blade and bench blade permanent marker, painter's tape and metre rule.

Product number: 7 230 34 62 00 0

Details

- + Outstanding ergonomics through compact and simple construction for optimal mobility of the shears.
- + Good curve precision with low sheet-metal distortion.
- + Four-fold reversing blade for clean and burr-free cutting with low operating costs.
- + Perfect for trimming and cutting.
- + Unrestricted view of the cutting line.
- + Motor with outstanding performance and stability.
- + 5 metre cable.
- + Stainless steel up to 1.0 mm.

Price includes

- + 2 plunger blade and bench blade (31308072000) fitted
- + 1 socket head wrench 2 mm
- + 1 permanent marker (32133037000)
- + 1 metre rule (18750283000)
- + 1 hand guard, fitted
- + 1 x 3 mm socket head wrench
- + 1 painter's tape (32133038000)
- + 1 tool case (L-BOXX 136)

Product feature

- + Reversing blade
- + Hand guard
- + Adjustable stroke

Application

Curve cuts



Coil sections



Interior cut-outs



Notches



- + suitable
- ++ well suitable

Technical data

TECHNICAL DATA

Input	350 W
Output	210 W
Strokes	2,300 - 4,800 rpm
Cutting speed	8 - 12 m/min
Steel up to 400 N/mm ²	1.6 mm
Steel up to 600 N/mm ²	1.2 mm
Steel up to 800 N/mm ²	1 mm
Non-ferrous metals up to 250 N/mm ²	2 mm
Rad. of smallest curve	15 mm
Cable with plug	5 m
Weight according to EPTA	1.70 kg
Weight according to EPTA	1.70 kg

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Uncertainty of measured value KpA	82,5 dB 3 dB
Sound power level LWA Uncertainty of measured value KWA	93,5 dB 3 dB
Sound peak value LpCpeak Uncertainty of measured value KpCpeak	94,9 dB 3 dB
Vibration value 1 α_{hv} 3-way Uncertainty of measured value K α	4,1 m/s ² 1,5 m/s ²

Application examples

