

BLK 2.0 E

Nibbler up to 2 mm

Compact nibbler with unlimited curve precision for corners and edges.

Product number: 7 232 40 60 24 1

Details

- > High curve precision due to special cutting head geometry. Nibbler can turn on the spot.
- > Especially well-suited for cutting edged sheet metals with a minimum bend radius of 3 mm.
- > Cutting direction setting can be changed in 45° steps up to 360° using tool-free pivoting cutting head.
- > QuickIN clamping system.
Optimal ergonomics.
- > Motor with outstanding performance and stability.
- > Ideal for cut-outs.
- > Optimally suited for template cuts.
- > Chip protection mesh on vent slots.
- > 5 metre cable.
- > Stainless steel up to 1.0 mm.

Price includes

- ✓ 1 die (3 13 09 040 00 2)
- ✓ 1 punch (6 36 02 051 00 9)

Product feature

- ✓ Cutting direction: 8x45°
- ✓ QuickIN



Application

Curve cuts



Cut-outs



★ suitable
★★ well suitable

Technical data

TECHNICAL DATA

Input	350 W
Output	210 W
Strokes	500 - 1,000 rpm
Cutting speed	1 m/min
Steel up to 400 N/mm ²	2 mm
Steel up to 600 N/mm ²	1.5 mm
Steel up to 800 N/mm ²	1 mm
Non-ferrous metals up to 250 N/mm ²	2.5 mm
Cutting width	8 mm
Immersion Ø with die	18 mm
Rad. of smallest curve (inside/outside)	4 / 0 mm
Cable with plug	5 m
Weight according to EPTA	1.80 kg

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Uncertainty of measured value KpA	80 dB 3 dB
Sound power level LWA Uncertainty of measured value KWA	91 dB 3 dB
Sound peak value LpCpeak Uncertainty of measured value KpCpeak	91 dB 3 dB
Vibration value 1 αhv 3-way Uncertainty of measured value Kα	7,3 m/s ² 1,5 m/s ²

Application examples