



ASCD 18-300 W2 AS Ready-to-use Set

User set contains a cordless impact wrench/driver

Cordless impact wrench/driver with 1/2" square head tool mounting. The user set includes 3-part set of impact sockets (17 / 19 / 21 mm) and circlip. Without battery or charger.

Product number: 7 115 10 63 00 0

Details

- + For extreme precision work: The ASCD 18-300 W2 AS with electronic torque setting (6 levels) prevents screw heads from shearing off.
- + Be ready to go instantly with tool and appropriate accessories for driving metric screws.
- + 3-part set of impact sockets with appropriate circlip for widths across flats of 17 mm, 19 mm and 21 mm.
- + VARIO 1/2" adapter, available as an extra and developed by FEIN, suitable for all VARIO accessories for simple and mechanical drilling, countersinking, tapping, recutting and cleaning of through holes up to a maximum of M18. Turns the impact wrench/driver into a taper, thereby adding a whole new tool to the range of applications.
- + Brushless FEIN PowerDrive motor with 30 % higher efficiency and long service life.
- + 1/2" square for holding sockets.
- + Metric screws up to M18 (8.8).
- + 10% more torque in reverse running to loosen screws which are extremely tight.
- + Robust solid metal impact gear.
- + Contact guard on gearbox head.
- + Up to 600 screw connections (M18) with one battery charge (ProCORE 4 Ah).
- + Bit and belt holder on the side for ergonomic and flexible handling.
- + Compatible with Bosch Professional 18 V batteries (available since 2008) and AMPShare batteries.
- + Maximum work progress with AMPShare 18V storage batteries: COOLPACK 1.0 technology ensures a longer storage battery life compared with batteries without COOLPACK technology and therefore makes longer operating periods possible. ECP protects the storage battery against overload, overheating and total discharge.
- + Ideally equipped for every form of use. Mobile working with the L-BOXX system.

Price includes

- + 1 x ASCD 18-300 W2 AS (including belt clip, bit holder)
- + 1 x set of impact sockets
- + 1 x locking spring
- + 1 tool case (L-Boxx 136)

Technical data

TECHNICAL DATA

Battery voltage	18 V
Battery compatibility	Li-ion / ProCORE Li-ion
Battery interface	18 V AMPShare

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Uncertainty of measured value KpA	99,2 dB 3 dB
Sound power level LWA Uncertainty of measured value KWA	107,2 dB 3 dB



FEIN

Motor	brushless	Sound peak value	121,5 dB
Speed, no load	0 - 1700 rpm	LpCpeak	3 dB
Impacts	0 - 3400 rpm	Uncertainty of measured value	
Max. torque	290 Nm	KpCpeak	
Torque levels	6	Vibration value 1 α_{hv} 3-way	α_h 15,0 m/s ²
Tool Holder	1/2 in Outer square	Uncertainty of measured value	1,5 m/s ²
Max. metric screw	M18 (8.8)	K α	
Wood screw Ø	8 x 300 mm		
Weight without storage battery	1.20 kg		

Application examples



Powered by **BOSCH**

Kompatibel mit
AMPShare-/ Bosch
Professional 18 V
Akkus. | Compatible
with AMPShare/Bosch
Professional 18 V batteries. | Compatible avec
les batteries 18 V AMPShare/Bosch Professional. |
Compatible con baterías AMPShare/Bosch
Professional de 18 V. | Compatibile con le batterie
AMPShare / Bosch Professional da 18 V.

