



## BOP 13-2

### Two-Speed Hand Drill up to 13 mm

Universal two-speed drill, up to 13 mm with ideal speed range for steel and stainless steel.

Product number: 7 205 55 60 00 0

### Details

- + Mechanical two-speed gearbox for optimum speed adjustment for a wide range of uses.
- + FEIN high-power motor with good speed stability for constant drilling progress in almost any application.
- + Metal gear head and distortion-free barrel-type motor housing for superb service life.
- + Reversible.
- + High-precision metal drill chuck.
- + High concentricity.
- + Self-tightening drill chuck clamping jaws.
- + FEIN Sensitive Handle.
- + Variable speed control.
- + 5 metre cable.
- + 43 mm diameter collar for use in the drill jig.

### Price includes

- + 1 SUPRA SKE single sheath metal quick clamping drill chuck
- + 1 additional handle

### Product feature

- + Reversible rotation
- + Acceleration electronics

### Application



Twist drilling

++

Tapping

++

Countersinking

++

+ suitable

++ well suitable

## Technical data

### TECHNICAL DATA

Input	550 W
Output	300 W
Speed, full load	0 - 440 / 0 - 1,300 rpm
Speed, no load	0 - 680 / 0 - 2,200 rpm
Torque at max. output power	20 / 7 Nm
Stall torque	50 / 16 Nm
Drill chuck clamping width	1.5 - 13 mm
Capacity in steel Ø	13 mm
capacity in Ø stainless steel	13 mm
Capacity in alu Ø	16 mm
Capacity in wood Ø	37 mm
Tapping	M 10
Thread of spindle	1/2"-20 UNF

### VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Uncertainty of measured value KpA	82 dB 3 dB
Sound power level LWA Uncertainty of measured value KWA	93 dB 3 dB
Sound peak value LpCpeak Uncertainty of measured value KpCpeak	96 dB 3 dB
Vibration value 1 $\alpha_{hv}$ 3-way Uncertainty of measured value K $\alpha$	$\alpha_{h,D}$ 3,0 m/s <sup>2</sup> 1,5 m/s <sup>2</sup>

Collar Ø	43 mm
Width across corners	23 mm
Cable with plug	5 m
Weight according to EPTA	2.00 kg
Weight according to EPTA	2.00 kg

## Application examples

