

BOP 6 set

Hand Drill up to 6 mm

Fast-running single-speed drill with good speed stability, up to 6 mm in steel in metal construction.

Product number: 7 205 52 61 00 0

Details

- > Optimum speed for lower diameters and therefore economic working with efficient use of the machine.
- > FEIN high-power motor with good speed stability for constant drilling progress in almost any application.
- > Metal gear head and distortion-free barrel-type motor housing for superb service life.
- > Reversible.
High-precision metal drill chuck.
- > High concentricity.
- > Self-tightening drill chuck clamping jaws.
- > FEIN Sensitive Handle.
- > Variable speed control.
- > 5 metre cable.
- > 43 mm diameter collar for use in the drill jig.

Price includes

- ✓ 1 SUPRA SKE single sheath metal quick clamping drill chuck
- ✓ 1 additional handle
- ✓ 1 plastic carrying case

Product feature

- ✓ Reversible rotation
- ✓ Acceleration electronics



FEIN

Application

Twist drilling



★ suitable

★★ well suitable



Technical data

TECHNICAL DATA

Input	500 W
Output	270 W
Speed, full load	0 - 2,700 rpm
Speed, no load	0 - 4,000 rpm
Torque at max. output power	3.5 Nm
Stall torque	9 Nm
Drill chuck clamping width	0.5 - 10 mm
Capacity in steel Ø	6 mm
capacity in Ø stainless steel	6 mm
Capacity in alu Ø	10 mm
Capacity in wood Ø	20 mm
Thread of spindle	1/2 in-20 UNF
Collar Ø	43 mm
Width across corners	23 mm
Cable with plug	5 m
Weight according to EPTA	1.70 kg

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Uncertainty of measured value KpA	82 dB 3 dB
Sound power level LWA Uncertainty of measured value KWA	93 dB 3 dB
Sound peak value LpCpeak Uncertainty of measured value KpCpeak	96 dB 3 dB
Vibration value 1 α_{hv} 3-way Uncertainty of measured value K α	$\alpha_{h,D}$ 4,0 m/s ² 1,5 m/s ²