



## SCT 5-40 X

### Dry wall screw gun, up to 5 mm

The specialist tool for drywall and interior work with quiet clutch.

Product number: 7 213 13 00 23 0

## Details

- > Speed-optimised; for rapid fixing of plasterboard to wood or metal frames.
- > Silent FEIN CLIC-STOP clutch for working in offices, hospitals etc. without causing a disturbance.
- > The depth stop supplied means that drywall is not damaged and you need simply grout after screwdriving.
- > One of the lightest screwdrivers in its class.
- > Market-leading ergonomics with FEIN Sensitive handle.
- > Point placement accuracy with infinitely variable electronic speed setting.
- > FEIN high-power motor.
- > Vibration-free stop.
- > Rapid changeover to collated strips.
- > Easily adjustable and replaceable depth stop.
- > Dustproof stop sleeve.
- > Extremely lightweight.
- > Practical hand strap.

## Price includes

- ✓ 1 hand strap
- ✓ 1 belt clip
- ✓ 1 depth stop, dust-proof protection
- ✓ 1 magnetic holder for bits ¼"
- ✓ 1 bit ¼" for cross-slotted screws size 2 / Phillips (form H) with dust-protection ring



## Technical data

### TECHNICAL DATA

Input	450 W
Output	250 W
Speed, full load	0 - 2,700 rpm
Speed, no load	0 - 4,000 rpm
Max. torque (hard/soft)	12 / - Nm
Screw Ø	5 mm
Rapid change chuck	1/4 in
Cable with plug	5 m
Weight according to EPTA	1.30 kg

### VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Uncertainty of measured value KpA	81 dB 3 dB
Sound power level LWA Uncertainty of measured value KWA	92 dB 3 dB
Sound peak value LpCpeak Uncertainty of measured value KpCpeak	98 dB 3 dB
Vibration value 1 $\alpha_{hv}$ 3- way Uncertainty of measured value K $\alpha$	0,8 m/s <sup>2</sup> 1,5 m/s <sup>2</sup>

## Application examples

