



SCS 4.8-25

Self-drilling Screwdriver up to 4.8 mm

One of the lightest self-drilling screwdriver in its class for roof and facade construction.

Product number: 7 213 04 00 23 9

Details

- > Safe working with self-drilling and thread-moulding screws up to 4.8 mm with or without sealing disc. It is also suitable for wing screws.
- > Lightweight drill/driver for fatigue-free working in roof and facade construction as well as heating, air conditioning and ventilation.
- > Adjustable, power-sensitive FEIN universal clutch for optimum configuration of torque when working without depth stop.
- > FEIN high-power motor.
- > Practical hand strap.

Price includes

- ✓ 1 depth stop
- ✓ 1 magnetic holder for bits ¼"
- ✓ 1 bit ¼" for cross-slotted screws size 2 / Phillips (form H) extra hard
- ✓ 1 hand strap
- ✓ 1 belt clip

Technical data

TECHNICAL DATA

Input	450 W
Output	250 W
Speed, full load	- 2,000 rpm
Speed, no load	- 2,500 rpm
Max. torque (hard/soft)	16 Nm
Screw Ø	4.8 mm
Rapid change chuck	1/4 in
Cable with plug	5 m

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Uncertainty of measured value KpA	82 dB 3 dB
Sound power level LWA Uncertainty of measured value KWA	93 dB 3 dB
Sound peak value LpCpeak Uncertainty of measured value KpCpeak	96 dB 3 dB
Vibration value 1 α_{hv} 3-way Uncertainty of measured value K α	1 m/s ² 1,5 m/s ²

Application examples

