



KBM 50 Q

Metal core drilling unit up to 50 mm

Lightweight and powerful 2-speed universal magnetic core drill with clockwise/anti-clockwise operation and maximum functionality for flexible working in the workshop and on the construction site.

Product number: 7 270 41 61 24 1

Details

- + Extremely low-wear tool design with swivel-mounted motor cable protection hose for tough use in industry and manual trades.
- + Perfect power-to-weight ratio thanks to compact, weight-optimised design and FEIN 1,200 W high-power motor with tacho electronics for high speed stability for reliable and economical working.
- + With clockwise/anti-clockwise operation, electronic speed setting and a 315 mm stroke range, this is a universal tool for core drilling, twist drilling, tapping, countersinking and reaming.
- + Simple operating concept avoids mix-ups and can be clearly seen by the user.
- + Convenient magnetic holding force display helps the user to reliably position the tool.
- + High magnetic holding force.
- + Integrated coolant tank delivers long core drill bit lives.
- + Feed handwheel can be moved from one side to the other.
- + Speed saving "memory function".
- + Personal safety switch.

Price includes

- + 1 coolant tank
- + 1 swarf hook
- + 1 contact guard
- + 1 lashing strap
- + 1 centering pin
- + 1 case

Product feature

- + Electronic magnetic holding force
- + Reversible rotation
- + Memory function
- + Magnetic holding force display
- + Variable speed control
- + Speed-controlled electronics (tacho)

Application



Core drilling in metal with a Ø up to 35 mm	++
Core drilling in metal with a Ø up to 50 mm	++
Twist drills with drill chuck (DIN 338)	+
Tapping	++
Countersinking	++
Reaming	++
Working overhead	+
Installation work	++
Workshop jobs	++

+ suitable
 ++ well suitable

Technical data

TECHNICAL DATA

Input	1,200 W
Output	640 W
Load speed in speed 1	130 - 260 rpm
Load speed in speed 2	260 - 520 rpm
Carbide core drill bit max. Ø	50 mm
HSS core drill max. Ø	40 mm
Core drill, drilling depth max.	50 mm
Twist drill max. Ø	16 mm

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Uncertainty of measured value KpA	82,1 dB 5 dB
Sound power level LWA Uncertainty of measured value KWA	93,1 dB 5 dB
Sound peak value LpCpeak Uncertainty of measured value KpCpeak	96,2 dB 5 dB
Vibration value 1 α_{hv} 3-way Uncertainty of measured value K α	< 2,5 m/s ² 1,5 m/s ²

Tapping	M 16
Countersinking max. Ø	31 mm
Reaming max. Ø	16 mm
Core drill holder	3/4 in Weldon
Changing the core bit	tool-free
Stroke	145 mm
Total stroke range	315 mm
Cable with plug	4 m

Application examples

