



F-IRON Cut 57 AS

Compact cordless circular saw for metal

Powerful cordless metal circular saw for rapid, precise cold cuts in sheet metals, pipes and profiles with a cutting depth of up to 57 mm.

Product number: 7 136 04 61 00 0



Details

- High performance low weight: 50% more material is removed than with standard metal circular saws as the brushless motor, ProCORE battery and optimally coordinated saw blade interact perfectly. And the tool weighs just 3 kg.
- Housing and safety hood made from die-cast aluminium and swarf collecting vessel made from material with low flammability for maximum protection from hot metal chips with sharp edges. The user has an unobstructed view of the cutting line at all times thanks to the LED working lamp.
- Pipes, profiles, metal grilles and sheet metals with a cutting depth of up to 57 mm can be sawn rapidly and precisely. Guide rail adapter for straight, long cuts – compatible with guide rails from Makita, BOSCH, Festool, Mafell.
- Manual speed setting (6 levels) for optimum results with a whole host of materials and no rework.
- Cold cuts for cuts with virtually no sparks or burrs.
- The LED light is activated in advance by the release switch.
- Safety hood closes in < 0.3 s even after 50 000 cycles.

- Better handling low weight, ergonomic handles including Softgrip for right- and left-handed users.
- Electronic user protection: Efficient brake (0.2 s), temperature-based shutdown to avoid permanent damage to tool and battery, restart protection, dead man's switch.
- Large swarf collecting vessel made from material with low flammability for long intervals between emptying.
- Heat-resistant, scratch-resistant and impactresistant housing made from die-cast aluminium.
- Compatible with all 18 V AMPShare ProCORE batteries and chargers for even more power and flexibility. Also suitable for 18 V Bosch Professional cordless devices.
- Maximum work progress with AMPShare 18V ProCORE batteries: COOLPACK 2.0 technology delivers a 135% longer battery life. State-of-theart cell technology and intelligent battery management deliver 87% more power than with conventional batteries. "Electronic Cell Protection" (ECP) protects the battery from overload, overheating and total discharge.
- Ideally equipped for every form of use. Mobile working with the L-BOXX system.

Price includes

- + 1 circular saw blade for construction steel
- + 1 socket head wrench 5 mm
- + 1 parallel stop

Technical data

TECHNICAL DATA

- + 1 swarf collecting vessel, fitted
- + 1 guide rail adapter
- + 1 plastic tool case (L-BOXX 238)

VIBRATION AND SOUND EMISSION VALUES



Battery	voltage
---------	---------

Battery compatibility

Battery interface

Speed, no load

Max. saw blade thickness

Saw blade Ø

Mounting hole Ø

Width

Height

Length

Steel up to 400 N/mm²

Non-ferrous metals up to 250 N/mm²

Max. cutting depth

Dimensions of base plate

Weight without storage battery

	18 V	SOU Unce
	Li-ion / ProCORE Li-ion	КрА
	18 V AMPShare	Sou Unce KWA
	1,300 - 2,800 rpm	Sou
S	2 mm	LpC Unce
	150 mm	КрС
	20 mm	Vibr way ^{Vibra}
	179 mm	Unc
	249 mm	valu
	287 mm	
	24 mm	
)	40 mm	
	57 mm	
ē	256 x 131 mm	

18 V

Sound pressure level LpA Uncertainty of measured value KpA

Sound power level LWA Uncertainty of measured value KWA

Sound peak value LpCpeak Uncertainty of measured value KpCpeak

Vibration value 1 αhv 3way Vibration value 2 αhv 3-way

Uncertainty of measured value K**a**

99,2 dB 3 dB

107,2 dB _{3 dB}

122,7 dB

3 dB

1,1 m/s²

1,1 m/s²

1,5 m/s²

Application examples

3.05 kg

















