



BLK 5.0 E

Nibbler up to 5 mm

Powerful nibbler for heavy dismantling and cutting applications.

Product number: 7 232 47 61 24 0

Details

- + Suited to cuts over 90° edges, for example on guard rails or during tank decommissioning.
- + Incredible power delivered by the 1700 W motor while also offering outstanding ergonomics and optimum power-to-weight ratio.
- + Extensive user protection: restart protection, blocking protection, overload protection, soft start.
- + Cutting direction: 4 x 90°, can be adjusted without the need for tools.
- + Variable stroke.
- + Tool-free quick change system for die and punch.
- + Ergonomic handle suited to guiding in all directions.
- + Chip protection mesh in fan area.
- + Wide range of accessories.

Price includes

- + 1 die 5, steel (31309107000) fitted
- + 1 punch 5/P5 steel (31309141000) fitted
- + 1 additional handle fitted

Product feature

- + Cutting direction
- + Adjustable stroke
- + QuickIN
- + Additional handle

Application

Curve cuts



Interior cut-outs



Profile sections



Notches





+ suitable
++ well suitable

Technical data

TECHNICAL DATA

Input	1,700 W
Output	1,000 W
Strokes	820 rpm
Cutting speed	1,5 m/min
Steel up to 400 N/mm ²	5 mm
Steel up to 600 N/mm ²	3.3 mm
Steel up to 800 N/mm ²	2.5 mm
Non-ferrous metals up to 250 N/mm ²	7 mm
Cutting width	8 mm
Immersion Ø with die	43 mm
Rad. of smallest curve (inside/outside)	90 / mm
Cable with plug	4 m
Weight according to EPTA	3.80 kg
Weight according to EPTA	3.80 kg

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA
Uncertainty of measured value
KpA

85 dB
3 dB

Sound power level LWA
Uncertainty of measured value
KWA

96 dB
3 dB

Sound peak value
LpCpeak
Uncertainty of measured value
KpCpeak

100 dB
3 dB

Vibration value 1 α_{hv} 3-way
Uncertainty of measured value
K α

10 m/s²
1,5 m/s²

Application examples



FEIN

