



## **ABLK 18 1.3 CSE AS Set 2x 5 Ah**

### **Cordless nibbler up to 1.3 mm**

Compact and curve-compatible nibbler for roof and façade construction. Precise cuts in corrugated sheet metal up to 1.3 mm. Includes battery charger GAL 1880 CV AS, 2x Li-ion storage batteries GBA 18V 5.0 Ah AS, additional punch and die set, permanent marker, painter's tape and metre rule.

Product number: 7 132 10 64 00 0

## Details

- + 66 m cutting capacity (in 0.8 mm sheet metal) with one battery charge (5 Ah).
- + Cutting direction setting can be changed in 45° steps up to 360° using tool-free pivoting cutting head.
- + Optimum handling due to extremely slim gearbox head.
- + 1.9 m/min cutting speed for excellent work progress.
- + Variable cutting speed due to electronically adjustable speed control.
- + Brief overlapping area up to 2.6 mm.
- + Rotating punch for a service life which is now up to 30 % longer.
- + Proven MultiMaster motor with outstanding performance and stability.
- + QuickIN quick change system for die and punch.
- + Low operating costs. Punch and die are replaced independently of one another.
- + Compatible with AMPShare/Bosch Professional 18 V batteries.
- + Maximum work progress with AMPShare 18V storage batteries: COOLPACK 1.0 technology ensures a longer storage battery life compared with batteries without COOLPACK technology and therefore makes longer operating periods possible. ECP protects the storage battery against overload, overheating and total discharge.
- + Ideally equipped for every job. Mobile working with the L-BOXX system.
- + State-of-the-art cell technology and intelligent battery management deliver 87% more power than with conventional batteries.

## Price includes

- + 1 die for corrugated sheet metal (30109169009) fitted
- + 1 punch (6 36 02 050 00 0)
- + 1 punch and die set (30109169030)
- + 1 permanent marker (32133037000)
- + 1 painter's tape (32133038000)
- + 1 metre rule (18750283000)
- + 2 Li-Ion storage battery GBA 28V 5.0 Ah AS (92604346020)
- + 1 rapid charger GAL 1880 CV AS (92604335010)
- + 1 tool case (L-Boxx 136)

## Product feature

- + Rotating round punch
- + Cutting direction
- + QuickIN
- + Adjustable stroke

## Application

Curve cuts



Coil sections





# FEIN

Interior cut-outs

++

Profile sections

++

Notches

++

+ suitable

++ well suitable

## Technical data

### TECHNICAL DATA

Battery voltage

18 V

Battery compatibility

Li-ion / ProCORE Li-ion

Battery interface

18 V AMPShare

Strokes

1 000 - 1 600 rpm

Cutting speed

1.9 m/min

Steel up to 400 N/mm<sup>2</sup>

1.3 mm

Steel up to 600 N/mm<sup>2</sup>

0.8 mm

Steel up to 800 N/mm<sup>2</sup>

0.6 mm

Non-ferrous metals up to  
250 N/mm<sup>2</sup>

2 mm

Cutting width

4 mm

Immersion Ø with die

19 mm

Rad. of smallest curve  
(inside/outside)

15 / 20 mm

Weight without storage  
battery

1.68 kg

### VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA  
Uncertainty of measured value  
KpA

82,2 dB  
3 dB

Sound power level LWA  
Uncertainty of measured value  
KWA

93,2 dB  
3 dB

Sound peak value  
LpCpeak  
Uncertainty of measured value  
KpCpeak

103,3 dB  
3 dB

Vibration value 1  $\alpha_{hv}$  3-  
way  
Uncertainty of measured value  
K $\alpha$

ah 3,8 m/s<sup>2</sup>  
1,5 m/s<sup>2</sup>



# FEIN

## Application examples

