



## ASCD 18-300 W2 Select

### Cordless Impact Wrench

Cordless impact wrench with brushless motor and 6 torque settings. For metric screw applications up to M18.

Product number: 7 115 06 64 09 0

### **Details**

- → Brushless FEIN PowerDrive motor with 30% greater efficiency and longer service life.
- + 6-Step electronic torque setting prevents shearing of screw heads.
- + 10% higher torque in reverse.
- → MultiVolt-interface. Cordless tool can be used with all FEIN li-ion batteries (12-18 V).
- + 1/2" square drive for mounting impact sockets.
- + Robust, solid metal impact gearbox.
- + Touch guard on drive head.
- + Compact design.

- + 600 screw applications (11/16 in [M18]) with one battery charge (6 Ah).
- + One charger for all voltage classes of FEIN Liion batteries.
- The battery capacity can be read directly on the battery.
- + FEIN SafetyCell technology. Protects the battery and the machine from overloading, overheating and deep discharge.
- User safe with restart and electronic overload protection.
- + Metric bolts up to M18 (8.8).

#### Price includes

- + 1 belt clip
- + 1 tool case

+ 1 magnetic bit holder

#### Technical data

TECHNICAL DATA

VIBRATION AND SOUND EMISSION VALUES

Battery voltage

18 V

Sound pressure level LpA Measurement uncertainty of the measured value KpA 96,1 dB 3 dB



Battery compatibility

Li-ion / HighPower Li-

Battery interface

No load speed

Motor

Impacts per minute

Max. torque

Torque steps

Tool mount

Max. bolt

Wood screw dia.

Weight without battery

ions

MultiVolt

brushless

0 - 1,700

0 - 3,400

2567 [290] in/lbs[Nm]

1/2" square

M18 (8.8)

3/8 [8] x 11-3/4 [300]

in[mm]

2.20 [1.00] lbs[kg]

Sound power level LWA

Measurement uncertainty of the measured value KWA

Peak sound value LpCpeak

Measurement uncertainty of the measured value KpCpeak

Vibration value 1  $\alpha$ hv 3-

Measurement uncertainty of the measured value  $K\alpha$ 

107,1 dB

3 dB

118,2 dB

3 dB

 $\alpha$ h 16,1 m/s<sup>2</sup>

1,5 m/s<sup>2</sup>

# Application examples

