



ASCD 18-1000 W34

Cordless Impact Wrench

Cordless impact wrench with brushless motor and 6 torque settings. For metric screw applications up to M27.

Product number: 7 115 08 65 09 0

Details

- + 6-Step electronic torque setting prevents shearing of screw heads.
- + High torque up to 775 ft/lb for tightening and 1,105 ft/lb loosening screws up to 1-1/16 in [M 27].
- + Brushless FEIN PowerDrive motor with 30% greater efficiency and longer service life.
- + Maximum release torque of 1,105 ft/lb.
- + Secure connection of the impact socket at the output square drive thanks to the positive, accurate connection.
- + 3/4" external square for mounting impact sockets.
- + Robust, solid metal impact gearbox.
- + MultiVolt-interface. Cordless tool can be used with all FEIN li-ion batteries (12-18 V).
- + 130 screw applications (1-1/16 in [M 27]) with one storage battery charge (6 Ah).
- + One charger for all voltage classes of FEIN Li-ion batteries.
- + The battery capacity can be read directly on the battery.
- + FEIN SafetyCell technology. Protects the battery and the machine from overloading, overheating and deep discharge.

Price includes

- + 1 rapid charger ALG 80
- + 2 Li-ion battery packs (18 V / 6 Ah)
- + 1 tool case

Technical data

TECHNICAL DATA

Battery voltage

18 V

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA
Measurement uncertainty of the measured value KpA

93,6 dB dB
3 dB dB



| | | | |
|------------------------|-----------------------------------|---|---|
| Battery capacity | 6 Ah | Sound power level LWA Measurement uncertainty of the measured value KWA | 104,6 dB dB 3 dB dB |
| Battery compatibility | Li-ion / HighPower Li-ions | Peak sound value LpCpeak Measurement uncertainty of the measured value KpCpeak | 119,5 dB dB 3 dB dB |
| Battery interface | MultiVolt | Vibration value 1 α_{hv} 3-way Measurement uncertainty of the measured value K α | 12,9 m/s ² m/s ² 1,5 m/s ² m/s ² |
| Motor | brushless | | |
| No load speed | 0 - 1,800 | | |
| Impacts per minute | 0 - 2,200 | | |
| Max. torque | 9293 [1,050] in/lbs[Nm] | | |
| Torque steps | 6 | | |
| Tool mount | 3/4" Outer square | | |
| Max. bolt | M27 (8.8) | | |
| Wood screw dia. | 1/2 [12] x 23-5/8 [600] in[mm] | | |
| Weight incl. battery | 8.16 [3.70] lbs[kg] | | |
| Weight without battery | 6.61 [3.00] lbs[kg] | | |

Application examples



FEIN

