

BOP 10

Hand Drill up to 3/8 in

Compact and powerful single-speed power drill with 3/8 in capacity in steel, for installation work on site.

Product number: 7 205 53 60 09 0



Details

- + Flat, slim design requiring little clearance in corners, for installation work, even in tight locations and in corners.
- + FEIN high performance motor with excellent speed stability for steady drilling progress in practically every application.
- + Torsion-free, barrel-type motor housing with metal gear head for superb service life.
- + Reversible.
- + Precision metal 3-jaw chuck.
- + High concentricity.
- + Retracting chuck jaws.
- + FEIN Sensitive Handle.
- + Electronic start.
- + 16 ft. [5 m] cable.
- + 1-11/16 [43] in[mm] collar diameter for use in drill jigs.

Price includes

- + 1 Supra SKE single-collar, metal fast-acting 3-jaw chuck
- + 1 additional handle

Product feature

- + Forward/reverse operation
- + Electronic start

Application



FEIN

Twist drilling

++

Tapping

+

Countersinking

+

+ suitable

++ well suitable

Technical data

TECHNICAL DATA

Power consumption

500 W

Power output

270 W

Full load speed

0 - 900 rpm

No load speed

0 - 1,500 rpm

Torque at maximum
output power

80 [9] in/lbs[Nm]

Stall/ blocking torque

212 [24] in/lbs[Nm]

Chuck capacity

1/16 [1.5] - 1/2 [13]
in[mm]

Capacity in steel Ø

13/32 [10] in[mm]

Capacity in stainless
steel Ø

1/2 [10] in[mm]

Capacity in light alloy Ø

1/2 [15] in[mm]

Capacity in wood Ø

1-3/16 [30] in[mm]

Tapping

M 6

Drill shaft thread

1/2 in-20 UNF

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA
Measurement uncertainty of
the measured value KpA

82 dB
3 dB

Sound power level LWA
Measurement uncertainty of
the measured value KWA

93 dB
3 dB

Peak sound value

96 dB

LpCpeak
Measurement uncertainty of
the measured value KpCpeak

3 dB

Vibration value 1 α_{hv} 3-
way
Measurement uncertainty of
the measured value K α

$\alpha_{h,D}$ 3,0 m/s²

1,5 m/s²



FEIN

Clamping neck	1-3/4 [43] in[mm]
Minimum clearance	7/8 [23] in[mm]
Minimum clearance	23 mm
Cable with plug	16 [5] ft[m]
Weight	3.97 lbs

Application examples

