



GSZ 4-280 EL

Die Grinder 28,000 rpm

Extremely handy die grinder with long reach for light grinding and polishing work in especially difficult-to-reach spots.

Product number: 7 223 24 60 09 0

Details

- Long, narrow neck and a max. width of 8-1/4 in [210 mm] allows tool to reach deep into workpieces (e.g. grinding inside pipes).
- Innovative collets with wrap around collar for workpiece protection and to prevent the wrench
- slipping when changing tools.
- + Variable speed allows different tools to be used.
- → Motor and electronics protected against metal dust.
- + Replaceable rubber neck bearing casing.

Price includes

- + 1 collet Ø 1/4 in [6 mm]
- + Spanner SW17

+ Spanner size 3

Product feature

+ Long neck

Application



++ well suitable

VALUES

VIBRATION AND SOUND EMISSION

Cutting

Material removal

Grinding

Deburring

Brushing

+ suitable

Technical data

TECHNICAL DATA

Power consumption	350 W	Sound pressure level LpA Measurement uncertainty of the measured value KpA	83 dB 3 dB
Power output	170 W		
No load speed	13,000 - 28,000 rpm	Sound power level LWA Measurement uncertainty of the measured value KWA	94 dB 3 dB
Grinding wheel for max. Ø	3/4 [20] in[mm]	Peak sound value LpCpeak	95 dB
Collet for max. Ø	1/4 [6] in[mm]	Measurement uncertainty of the measured value KpCpeak	3 dB
Clamping neck	1-3/4 [43] in[mm]	Vibration value 1 α hv 3-way Measurement uncertainty of the measured value K α	4,8 m/s²
Milling machine max. dia.	1/2 [12] in[mm]		1,5 m/s²
Cable with plug	16.4 [5] ft[m]		

Application examples

Weight

3.31 lbs



