



# FEIN



## AJMU 137 PMQW 18V AS Set 2 x 8 Ah

Cordless Universal magnetic base drill up to 1-3/8 [35] in[mm]

Battery set with 2 x 8 Ah CORE batteries. Ideal for on-site work with limited power supply.

Product number: 7 170 05 63 09 0

## Details

- + Extremely durable cordless mag drill with a FEIN PowerDrive designed for up to 60,000 holes during a 300 h usage period.
- + Small and lightweight machine with up to 25% higher work progress with one-of-a-kind productivity and longer storage battery life as compared to competitors. With an 18 V 8 Ah AMPShare ProCORE storage battery, up to 31 holes per battery charge are possible (Carbide cutter, 11/16" dia., mild steel 1/2").
- + The lightest cordless mag drill in the world at only 26.9 lbs. This drill features forward/reverse, electronic speed control, and 10-1/4" stroke range for maximum flexibility in all applications (drilling, tapping, twist drilling, reaming and countersinking).
- + Intuitive operator controls located on the top of the drill motor for maximum visibility.
- + A Convenient magnetic holding force indicator supports the safe positioning of the tool.
- + Workplace Safety: Tilt sensor safety shutoff will shut down the drill in the event it should move or break free from the workpiece.
- + MK2 tool mount for direct use of industrial tools.
- + Secure position thanks to extra narrow permanent magnet with pre-magnetization for convenient and simple alignment.
- + "Memory function" speed storage.
- + COOLPACK 2.0 technology ensures a 135% longer battery service life, enabling longer operation time.
- + State-of-the-art cell technology and intelligent battery management deliver 87% more power than conventional batteries.
- + CORE 18 V Li-ion battery with Highpower cells, charge indicator and electronic cell protection (ECP). ECP protects batteries against overloading, overheating and deep discharge.
- + \* optional using accessory.
- + \*\* Maximum performance with AMPShare CORE 18 V 8.0 Ah / 12.0 Ah

## Price includes

- |  |   |
|--|---|
| + 1 cordless magnetic core drill                       | + 1 coolant pump                                      |
| + 1 safety strap                                       | + 1 chip hook   |
| + 1 centering pin dia. 1/4 x 3-9/16 [6.35 x 90] in[mm] | + 1 centering pin dia. 1/4 x 3-1/4 [6.35 x 82] in[mm] |
| + 1 centering pin dia. 1/4 x 4 [6.35 x 100] in[mm]     | + 1 chip guard  |
| + 1 drift  | + 2 CORE 18 V / 8.0 Ah Li-Ion batteries               |
| + 1 GAL18 V-160 AS rapid charger                       | + 1 tool case   |

## Product feature

- |                                      |                             |
|--------------------------------------|-----------------------------|
| + Magnet holding force display       | + Forward/reverse operation |
| + Electronic speed setting           | + Memory function           |
| + Speed-controlled tacho electronics | + Tilt sensor               |



**FEIN**

Application



Mag base drilling metal up to 1-1/2" dia.

++

Twist drilling with drill chuck

+

Twist drilling with MT fitting

++

Tapping

++

Countersinking

++

Reaming

++

Performing overhead work

++

Installation work

++

+ suitable

++ well suitable

## Technical data

### TECHNICAL DATA

Battery voltage

18 V

Battery compatibility

Li-ion / CORE 18 V Li-ions

Battery interface

18 V AMPShare

Motor

brushless

Full load speed

130 - 520 rpm

Tool mount

MT 2

Carbide cutter max. dia.

1-3/8 [35] in[mm]

HSS cutter max. dia.

1-3/8 [35] in[mm]

Cutter max. drilling depth

2 [50] (3 [75] )\* in[mm]

Sound pressure level LpA  
Measurement uncertainty of  
the measured value KpA

82,4 dB  
3 dB

Sound power level LWA  
Measurement uncertainty of  
the measured value KWA

93,4 dB  
3 dB

Peak sound value  
LpCpeak  
Measurement uncertainty of  
the measured value KpCpeak

97,1 dB  
3 dB

Vibration value 1  $\alpha_{hv}$  3-  
way  
Measurement uncertainty of  
the measured value K $\alpha$

$\alpha_{h,D}$  0,6 m/s<sup>2</sup>  
1,5 m/s<sup>2</sup>

### VIBRATION AND SOUND EMISSION VALUES

Twist drill max. dia.	3/4 [18] in[mm]
Tapping	1/2"
Max. countersinking dia.	1-1/4 [31] in[mm]
Reaming max. dia.	3/4 [18] in[mm]
Cutter holder	3/4" straight shank
Cutter change	tool-free
Stroke	5-5/16 [135] in[mm]
Total stroke range	10-1/4 [260] in[mm]
Magnetic holding force	2023 [9,000] lbs[N]
Magnetic base dimensions	7-11/16 [195] x 2-3/4 [70] in[mm]
Weight without battery	26.90 [12.20] lbs[kg]

## Application examples



