



Cordless MULTIMASTER AMM 700 1.7 Q Autoglas AS

Cordless oscillating multi-tool

Our best oscillating cordless MultiMaster for the automotive sector incl. extensive accessories for removing windshields and working on car bodies.

Product number: 7 129 37 62 09 0



Details

- Designed for removing windshields and working on car bodies.
- Anti-vibration system: Permanently safe, pleasant working conditions with minimum vibrations and outstanding noise damping.
- QuickIN: Tool change in under 3 seconds with a patented, tool-free, FEIN rapid-clamping system.
- + 12-sided mount for optimal torque transfer.
- 18 V FEIN PowerDrive motor: Especially powerful, virtually wear-free brushless motor with high efficiency, extremely high load handling and long service life.
- Tacho generator: Constant speeds, even under load, and infinitely variable electronic speed control.

- Metal drive head: High load capacity and maximum service life, since all drive head parts are made of metal.
- Electronic cell protection (ECP): ECP protects storage batteries against overloading, overheating and deep discharge.
- COOLPACK technology ensures a longer storage battery service life, enabling longer operation times.
- The battery capacity can be read directly on the battery.
- Compatible with AMPShare/Bosch Professional 18 V batteries from 2008 on.
- Perfectly equipped for any job with our L-BOXX system.

Price includes

- + 1 protective cover for accessory changes
- 2 U-shaped cutting blades, reinforced model (types 157 and 111)
- 2 L-shaped cutting blades, toothed (type 208)
- + 3 L-shaped cutting blades, serrated (type 207)
- + 1 whetstone (63719010014)
- + 2 Li-ion battery packs (18 V / 4 Ah)

Technical data

TECHNICAL DATA

- 1 straight cutting blade, offset, serrated (type 081)
- 1 L-shaped cutting blade, serrated (type 209)
- 2 U-shaped cutting blades, reinforced model, serrated (type 212)
- 1 straight cutting blade, offset, with adjustable roller stop (type 143)
- + 1 rapid charger GAL 1880 CV AS
- + 1 tool case (L-BOXX 136)

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Measurement uncertainty of the measured value KpA 77,9 dB 3 dB

Battery capacity

Battery voltage

4 Ah

18 V



Battery	compatibil	ity
---------	------------	-----

Battery interface


Oscillations

Tool mount

Tool change

Range

Weight without battery



Sound power level LWA Measurement uncertainty of the measured value KWA

Peak sound value

LpCpeak Measurement uncertainty of the measured value KpCpeak 85,9 dB 3 dB

91,7 dB

3 dB

Application examples



Compatible with AMPShare/Bosch Professional 18 V batteries.

Compatible avec les batteries 18 V AMPShare/Bosch Professional. | Compatible con baterías AMPShare/ Bosch Professional de 18 V.





