

FEIN cordless MultiMaster AFMM 18 QSL

Cordless oscillating multi-tool

The high performance, cordless universal system for interior construction and renovation with QuickIN and accessories for a wide range of applications.

Product number: 7 129 22 61 09 0

Details

- > FEIN Anti-Vibration System. Up to 70% less vibration due to complete decoupling of the outer motor housing. For durable safe work.
- > Starlock tool mount standard. Perfect accessory seating due to 3D profile. 100% lossless power transmission for up to 35% faster cutting speed.
- > QuickIN tool change. Patented, tool-free FEIN rapid clamping system for safe, convenient tool changes in under 3 seconds.
- > StarlockPlus for outstanding versatility due to access to the complete Starlock- and StarlockPlus accessory range.
- > DC motor. Proven motor technology with small size, efficiency and high torque.
- > Tacho generator. High-quality electronics for constant speed, even under load. infinitely variable electronic speed adjustment.
- > Metal drive head. High load capacity and maximum service life.
- > Integrated interface for additional system accessories, including depth stop.
- > Largest accessory range with Starlock and StarlockPlus mounts in FEIN quality.
- > FEIN SafetyCell technology. Protects the battery and the machine from overloading, overheating and deep discharge.
- > The battery capacity can be read directly on the battery.

Price includes

- ✓ 1 backing pad
- ✓ 1 HSS segment saw blade
- ✓ 1 rapid charger ALG 50
- ✓ 3 of each sanding sheet (grits 60, 80, 120, 180)
- ✓ 1 E-Cut Long-Life saw blade 2-9/16 in (65 mm) (type 161)
- ✓ 2 Li-ion battery packs (18 V / 3 Ah)
- ✓ 1 rigid scraper blade
- ✓ 1 universal E-Cut saw blade 1-3/4 in (44 mm) (type 152)
- ✓ 1 tool case

Product feature

- ✓ Mechanical interconnection



Technical data

TECHNICAL DATA

Battery voltage	18 V
Battery capacity	3 Ah
Battery compatibility	Li-ion / HighPower Li-ions
Battery interface	18 V
Oscillations	11,000 - 18,500 opm
Tool mount	StarlockPlus
Tool change	QuickIN
Range	2 x 1,7°
Weight incl. battery	3.97 [1.80] lbs[kg]

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Measurement uncertainty of the measured value KpA	74 dB 3 dB
Sound power level LWA Measurement uncertainty of the measured value KWA	85 dB 3 dB
Peak sound value LpCpeak Measurement uncertainty of the measured value KpCpeak	87 dB 3 dB

Application examples