



MULTIMASTER MM 700

Max

Oscillating MultiTools - MM 700

Top in its performance class, our MULTIMASTER 700 makes quick work of professional interior construction and renovation jobs.. Includes a bimetal saw blade for working in wood, metal and plastic.

Product number: 7 229 68 63 09 0

Details

- + Anti-vibration system: Permanently safe, pleasant working conditions with minimum vibrations and outstanding noise damping.
- + StarlockMax tool mounting: Work faster and with higher precision thanks to 100% no-loss power transmission.
- + QuickIN: Tool change in under 3 seconds with a patented, tool-free, FEIN rapid-clamping system.
- + With the StarlockMax tool mounting, you have access to around 180 FEIN accessories in the Starlock, StarlockPlus and StarlockMax performance categories.
- + 450 W FEIN high-performance motor: Durable, overload-proof, high-performance motor with high proportion of copper for higher cutting speed and ultra-rapid work progress.
- + Tacho generator: Constant speeds, even under load, and infinitely variable electronic speed control.
- + Metal drive head: High load capacity and maximum service life, since all drive head parts are made of metal.
- + Mechanical interface: For stationary use in the table or drill jig holders, or to attach depth stops.
- + Industrial cable: Large operating radius thanks to the 5 m, fine-stranded rubber-clad cable in industrial quality.
- + Electronic safety cut-off – protection for users if the saw blade blocks, for example.
- + Perfectly equipped for any job with our L-BOXX system.

Price includes

- + 1 universal E-Cut saw blade 1-3/4 in (44 mm) (type 152)
- + 1 tool case (L-BOXX 136)

Product feature

- + Mechanical interconnection

Technical data

TECHNICAL DATA



FEIN

VIBRATION AND SOUND EMISSION VALUES

Power consumption	450 W	Sound pressure level LpA Measurement uncertainty of the measured value KpA	84,1 dB 3 dB
Power output	250 W		
Oscillations	- opm	Sound power level LWA Measurement uncertainty of the measured value KWA	92,1 dB 3 dB
Tool mount	StarlockMax		
Tool change	QuickIN	Peak sound value LpCpeak Measurement uncertainty of the measured value KpCpeak	97,5 dB 3 dB
Range	2 x 2,0°		
Cable with plug	16.4 [5] ft[m]		
Weight	3.53 [1.60] lbs[kg]		

Application examples

