



# Cordless MULTIMASTER AMM 500 Plus AS

## Cordless oscillating multi-tool

The high-performance cordless MultiTool for rapid work progress (both interior construction and renovation) in the variant without a storage battery and charger – with a bi-metal saw blade for wood, metal, and plastics.

Product number: 7 129 38 62 09 0

## Details

- + Anti-vibration system: Permanently safe, pleasant working conditions with minimum vibrations and outstanding noise damping.
- + StarlockPlus tool mounting: Work faster and with higher precision thanks to 100% no-loss power transmission.
- + QuickLIN: Tool change in under 3 seconds with a patented, tool-free, FEIN rapid-clamping system.
- + With the StarlockPlus tool mounting, you have access to around 100 FEIN accessories in the Starlock and StarlockPlus performance categories.
- + DC motor: Effective, high-torque motor technology for output that is virtually identical to that of the model with a cord.
- + Tacho generator: Constant speeds, even under load, and infinitely variable electronic speed control.
- + Metal drive head: High load capacity and maximum service life, since all drive head parts are made of metal.
- + Mechanical interface: For stationary use in the table or drill jig holders, or to attach depth stops.
- + Electronic cell protection (ECP): ECP protects storage batteries against overloading, overheating and deep discharge.
- + COOLPACK technology ensures a longer storage battery service life, enabling longer operation times.
- + The battery capacity can be read directly on the battery.
- + Compatible with AMPShare/Bosch Professional 18 V batteries from 2008 on.
- + Perfectly equipped for any job with our L-BOXX system.

## Price includes

- + 1 universal E-Cut saw blade 1-3/4 in (44 mm) (type 152)
- + 1 tool case (L-BOXX 136)

## Product feature

- + Mechanical interconnection

## Technical data

## TECHNICAL DATA

Battery voltage	18 V
Battery compatibility	Li-ion / CORE 18 V Li-ions
Battery interface	18 V AMPShare
Oscillations	11,000 - 18,500 opm
Tool mount	StarlockPlus
Tool change	QuickIN
Range	2 x 1,7°
Weight without battery	2.87 [1.30] lbs[kg]

## VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Measurement uncertainty of the measured value KpA	80,7 dB 3 dB
Sound power level LWA Measurement uncertainty of the measured value KWA	88,7 dB 3 dB
Peak sound value LpCpeak Measurement uncertainty of the measured value KpCpeak	93 dB 3 dB

## Application examples



Compatible with  
AMPShare/Bosch  
Professional  
18 V batteries. |

Compatible avec les batteries 18 V  
AMPShare/Bosch Professional. |  
Compatible con baterías AMPShare/  
Bosch Professional de 18 V.

