



# FEIN



## Cordless MULTIMASTER AMM 700 Max Top 4 Ah AS

### Cordless oscillating multi-tool

Top in its performance class, our MULTIMASTER 700 makes quick work of professional interior construction and renovation jobs. Includes accessories for sawing in wood, metal, plastics, removing tiles, cutting silicone caulking and carpeting, and removing residual adhesive and tile adhesive.

Product number: 7 129 36 61 09 0

## Details

- + Anti-vibration system: Permanently safe, pleasant working conditions with minimum vibrations and outstanding noise damping.
- + StarlockMax tool mounting: Work faster and with higher precision thanks to 100% no-loss power transmission.
- + QuickIN: Tool change in under 3 seconds with a patented, tool-free, FEIN rapid-clamping system.
- + With the StarlockMax tool mounting, you have access to around 180 FEIN accessories in the Starlock, StarlockPlus and StarlockMax performance categories.
- + 18 V FEIN PowerDrive motor: Especially powerful, virtually wear-free brushless motor with high efficiency, extremely high load handling and long service life.
- + Tacho generator: Constant speeds, even under load, and infinitely variable electronic speed control.
- + Metal drive head: High load capacity and maximum service life, since all drive head parts are made of metal.
- + Mechanical interface: For stationary use in the table or drill jig holders, or to attach depth stops.
- + Electronic cell protection (ECP): ECP protects storage batteries against overloading, overheating and deep discharge.
- + COOLPACK technology ensures a longer storage battery service life, enabling longer operation times.
- + The battery capacity can be read directly on the battery.
- + Compatible with AMPShare/Bosch Professional 18 V batteries from 2008 on.
- + Electronic safety cut-off – protection for users if the saw blade blocks, for example.
- + Perfectly equipped for any job with our L-BOXX system.

## Price includes

- |   |   |
|---|---|
| + 2 E-Cut standard saw blades, curved (1-3/8 [35] in[mm])     | + 2 E-Cut standard saw blades, curved (2-1/2 [65] in[mm]) |
| + 1 E-Cut Precision saw blade (1-3/8 [35] in[mm])             | + 1 E-Cut Precision saw blade (2-9/16 [65] in[mm])        |
| + 1 E-Cut Long Life saw blade (10 mm)                         | + 2 E-Cut Long Life saw blades (1-3/8 [35] in[mm])        |
| + 1 E-Cut Long Life saw blade (1-1/4 [32] in[mm])             | + 1 E-Cut Long Life saw blade (1-5/8 [42] in[mm])         |
| + 1 E-Cut Carbide Pro saw blade (1-1/4 [32] in[mm])           | + 1 segmented saw blade (Ø 3-3/8 [85] in[mm])             |
| + 1 carbide segment saw blade                                 | + 1 carbide rasp (triangular)                             |
| + 1 rigid scraper blade                                       | + 1 mushroom-shaped cutting blade 6 390 31 28 01 2        |
| + 1 Multi-knife   | + 1 perforated sanding pad                                |
| + 10 sanding sheets, perforated each (grits 60, 80, 120, 180) | + 1 dust extraction device                                |

- + 1 rapid charger GAL 1880 CV AS
- + 1 tool case (L-BOXX 136)

- + 2 Li-ion battery packs (18 V / 4 Ah)

## Product feature

- + Mechanical interconnection

## Technical data

### TECHNICAL DATA

Battery voltage	18 V
Battery capacity	4 Ah
Battery compatibility	Li-ion / CORE 18 V Li-ions
Battery interface	18 V AMPShare
Oscillations	10,000 - 19,500 opm
Tool mount	StarlockMax
Tool change	QuickIN
Range	2 x 2,0°
Weight without battery	2.43 [1.10] lbs[kg]

### VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA  
Measurement uncertainty of the measured value KpA

80,4 dB  
3 dB

Sound power level LWA  
Measurement uncertainty of the measured value KWA

88,4 dB  
3 dB

Peak sound value  
LpCpeak  
Measurement uncertainty of the measured value KpCpeak

92,5 dB  
3 dB

## Application examples



Compatible with  
AMPShare/Bosch  
Professional  
18 V batteries. |  
Compatible avec les batteries 18 V  
AMPShare/Bosch Professional. |  
Compatible con baterías AMPShare/  
Bosch Professional de 18 V.



