



ABSS 18 1.6 E AS Set

Cordless slitting shears for up to 1.6 mm

Handy, maneuverable and fast cordless slitting shears for cuts and cut-outs in sheet metal up to 16 gauge [1.6mm] in thickness. Includes BC 1880 CV AS charger, 2x CORE 18V 4.0 Ah AS lithium-ion batteries, additional curve cutter, permanent marker and painter's tape.

Product number: 7 130 05 65 09 0

Details

- + 590 [180] ft[m] cutting capacity (in 22 [0.8] gauge[mm] sheet metal) with one battery charge (4 Ah).
- + Rapid performance due to excellent view of the cutting line through the open-front cutting head.
- + Left and right curve cuts and distortion-free cutting possible with one continuous chip.
- + QuickIN for rapid, tool-free blade changing, with no further adjustment required.
- + Excellent ergonomics and low weight.
- + Cutting blade with outstanding service life.
- + Proven MultiMaster motor with outstanding power and durability.
- + Compatible with AMPShare/Bosch Professional 18 V batteries from 2008 on.
- + Maximum cutting speed with AMPShare 18V batteries: COOLPACK 2.0 technology ensures a longer battery service life in comparison to batteries without COOLPACK technology. It makes longer operation times possible. ECP protects batteries against overloading, overheating and deep discharge.
- + Perfectly equipped for any application. Mobile work with the L-BOXX system.
- + State-of-the-art cell technology and intelligent battery management deliver 87% more power than conventional batteries.

Price includes

- + 1 cutter blade (31308150009), mounted
- + 1 allen key 2,5 mm
- + 1 permanent marker (32133037000)
- + 2 Li-ion battery packs (18 V / 4 Ah)
- + 1 tool case (L-BOXX 136)
- + 1 pair of dies (31308153014), mounted
- + 1 blade for curves (31308151008)
- + 1 roll painter's tape (32133038000)
- + 1 rapid charger BC 1880 CV AS (92604335010)

Product feature

- + QuickIN
- + Full visibility of cutting line
- + Variable speed

Application

Curve cuts



Coil cuts



Inside cutouts



Profile cuts





Notches



+ suitable

++ well suitable

Technical data

TECHNICAL DATA

VIBRATION AND SOUND EMISSION VALUES

Battery voltage	18 V	Sound pressure level LpA Measurement uncertainty of the measured value KpA	74,3 dB 3 dB
Battery capacity	4 Ah		
Battery compatibility	Li-ion / CORE 18 V Li-ions	Sound power level LWA Measurement uncertainty of the measured value KWA	85,3 dB 3 dB
Battery interface	18 V AMPShare	Peak sound value LpCpeak Measurement uncertainty of the measured value KpCpeak	87,6 dB 3 dB
Strokes	2,200 - 3,500 spm		
Cutting speed	16.4 [5] - 26.2 [8] ft/min[m/min]	Vibration value 1 α_{hv} 3- way Measurement uncertainty of the measured value K α	ah 4,6 m/s ² 1,5 m/s ²
Steel 58,000 lbf/in ²	1/16 [1.6] in[mm]		
Steel 87,000 lbf/in ²	3/64 [1.2] in[mm]		
Steel 116,000 lbf/in ²	1/32 [0.8] in[mm]		
Non-ferrous metals up to 36,000 lbf/in ²	3/32 [2] in[mm]		
Cutting width	3/16 [5] in[mm]		
Radius of smallest curve	3-1/2 [90] (1-1/4 [30]) ¹ in[mm]		
Immersion dia.	1/2 [15] (1/4 [8]) ¹ in[mm]		
Weight without battery	2.73 [1.24] lbs[kg]		

Application examples

