



Corona HSS Dura 50 con inserción QuickIN

Recubrimiento de TiN para una excelente vida útil y las mejores propiedades de deslizamiento.

Medidas métricas, prof. de corte 50 mm.

45,70 € P.V.P. sin I.V.A.

N.º pedido: 6 31 33 150 06 8

Datos técnicos

DATOS GENERALES

Profundidad de corte

50 mm

Ø de taladrado

15 mm

Adaptable para las siguientes máquinas

Universal

- > KBM 65 U
- > KBM 50 Q
- > KBM 50 U
- > KBU 35 QW Fabricator M12 Tapping-Set 3/4 in Weldon
- > KBM 65 UQW
- > KBM 50 UQW
- > KBU 35 PQ
- > KBU 35 QW Structural Steel-Set 3/4 in Weldon
- > AKBU 35 PMQW 18 V AS Construction-Site 2x 8 Ah Set 3/4 in Weldon / HSS NOVA 50
- > KBU 35 PQW
- > KBU 35-2 QW
- > KBU 35 MQW
- > KBU 35 QW
- > KBU 35-2 Q
- > KBU 35 MQ
- > KBU 35 Q
- > AKBU 35 PMQW 18 V AS Construction-Site 1x 12 Ah Set 3/4 in Weldon / HSS NOVA 50
- > AKBU 35 PMQW AS Construction-Site Set 3/4 in Weldon / HSS NOVA 50
- > AKBU 35 PMQW 18 V AS Set 1x 12 Ah
- > AKBU 35 PMQW 18 V AS Set 2x 8 Ah
- > AKBU 35 PMQW AS
- > AKBU 35 PMQ AS



Automatic

> KBM 50 auto QW

> KBM 50 auto