



FEIN



Corona HSS Dura 50 con inserción 3/4 in Weldon

Recubrimiento de TiN para una excelente vida útil y las mejores propiedades de deslizamiento.

Medidas métricas, prof. de corte 50 mm.

47,85 € P.V.P. sin I.V.A.

N.º pedido: 6 31 34 190 07 6

Datos técnicos

DATOS GENERALES

Profundidad de corte

50 mm

Ø de taladrado

19 mm

Adaptable para las siguientes máquinas

Universal

- | | | |
|---|--|--|
| > AKBU 35 PMQ AS | Ah Set 3/4 in Weldon / HSS NOVA 50 | > KBU 35 PQW |
| > AKBU 35 PMQW AS | | > KBU 35 PQ |
| > AKBU 35 PMQW 18 V AS Set 2x 8 Ah | > AKBU 35 PMQW 18 V AS Construction-Site 2x 8 Ah Set 3/4 in Weldon / HSS NOVA 50 | > KBM 50 U |
| > AKBU 35 PMQW 18 V AS Set 1x 12 Ah | | > KBM 50 Q |
| > AKBU 35 PMQW AS Construction-Site Set 3/4 in Weldon / HSS NOVA 50 | > KBU 35 Q | > KBM 65 U |
| > AKBU 35 PMQW 18 V AS Construction-Site 1x 12 | > KBU 35 MQ | > KBU 35 QW Structural Steel-Set 3/4 in Weldon |
| | > KBU 35-2 Q | > KBU 35 QW Fabricator M12 Tapping-Set 3/4 in Weldon |
| | > KBU 35 QW | > KBM 50 UQW |
| | > KBU 35 MQW | > KBM 65 UQW |
| | > KBU 35-2 QW | |



Endurance

- > KBE 50-2
- > KBE 32
- > KBE 32 QW
- > KBE 36 MAGSPEED
- > KBE 36 QW MAGSPEED
- > KBE 36 QW MAGSPEED Fabrication Set

Automatic

- > KBM 50 auto
- > KBM 50 auto QW