



Inserto roscador

para macho de roscar según DIN 374/376

96,00 € P.V.P. sin I.V.A.

N.º pedido: 6 32 06 117 01 5

Datos técnicos

DATOS GENERALES

Roscas

M 6

Ø

4,5 mm

Cuadrado

3,4 mm

Adaptable para las siguientes máquinas

Universal

- | | | |
|--|---|-------------------------|
| > KBM 65 UQW | Ah Set 3/4 in Weldon / HSS NOVA 50 | Steel-Set 3/4 in Weldon |
| > KBM 50 UQW | | > KBM 50 Q |
| > KBU 35 QW Fabricator M12 Tapping-Set 3/4 in Weldon | > AKBU 35 PMQW AS Construction-Site Set 3/4 in Weldon / HSS NOVA 50 | > KBM 50 U |
| > KBM 65 U | > AKBU 35 PMQW 18 V AS Set 1x 12 Ah | > KBU 35 PQ |
| > AKBU 35 PMQW 18 V AS Construction-Site 2x 8 Ah Set 3/4 in Weldon / HSS NOVA 50 | > AKBU 35 PMQW 18 V AS Set 2x 8 Ah | > KBU 35 PQW |
| > AKBU 35 PMQW 18 V AS Construction-Site 1x 12 | > AKBU 35 PMQW AS | > KBU 35-2 QW |
| | > AKBU 35 PMQ AS | > KBU 35 MQW |
| | > KBU 35 QW Structural | > KBU 35 QW |
| | | > KBU 35-2 Q |
| | | > KBU 35 MQ |
| | | > KBU 35 Q |



Automatic

> KBM 50 auto QW

> KBM 50 auto