



FEIN



QuickIN-kiinnityksellä varustettu HSS Dura 25 - keernapora

TiN-pinnoite takaa erinomaisen käyttöiän ja parhaat liukuominaisuudet.

Metriset mitat, leikkuusyvyys 25 mm.

Tuotenumero: 6 31 33 280 06 7

tekniset tiedot

YLEISET OMINAISUUDET

Leikkuusyvyys

25 mm

Poraus-Ø

28 mm

Soveltuu seuraaville koneille

Universal

- > KBM 65 U
- > KBM 50 Q
- > KBM 50 UQW
- > KBM 65 UQW
- > KBM 50 U
- > KBU 35 QW Fabricator M12 Tapping-Set 3/4 in Weldon
- > KBU 35 QW Structural Steel-Set 3/4 in Weldon
- > KBU 35 PQ
- > KBU 35 PQW
- > KBU 35-2 QW
- > KBU 35 MQW
- > KBU 35 QW
- > KBU 35-2 Q
- > KBU 35 MQ
- > KBU 35 Q
- > AKBU 35 PMQW 18 V AS CONSTRUCTION SITE 2 x 8 Ah -sarja 3/4 in:n Weldon / HSS NOVA 50
- > AKBU 35 PMQW 18 V AS CONSTRUCTION SITE 1
- x 12 Ah -sarja 3/4 in Weldon / HSS NOVA 50
- > AKBU 35 PMQW AS CONSTRUCTION SITE -sarja 3/4 in Weldon / HSS NOVA 50
- > AKBU 35 PMQW 18 V AS Set 1x 12 Ah
- > AKBU 35 PMQW 18 V AS -sarja 2 x 8 Ah
- > AKBU 35 PMQW AS
- > AKBU 35 PMQ AS



Automatic

> KBM 50 auto QW

> KBM 50 auto