



Fresa a corona HSS Dura 25 con attacco QuickIN

Rivestimento superficiale TiN per una lunga durata e una migliore scorrevolezza.

Misure metriche, profondità di taglio 25 mm.

76.78 CHF IVA incl.

Numero d'ordine: 6 31 33 310 06 7

Specifiche tecniche

SPECIFICHE GENERALI

Profondità di taglio

25 mm

Ø foro

31 mm

Adatto per le seguenti macchine

Universal

- | | | |
|--|---|--|
| > KBU 35 MQ | > KBU 35 QW | Set con attacco Weldon da 3/4 in / HSS NOVA 50 |
| > KBU 35 Q | > KBU 35 PQW | |
| > KBM 65 U | > KBU 35-2 QW | > AKBU 35 PMQW AS |
| > KBM 50 Q | > KBU 35 MQW | Construction-Site Set con attacco Weldon da 3/4 in / HSS NOVA 50 |
| > KBM 50 U | > KBU 35-2 Q | |
| > KBU 35 QW Structural Steel-Set 3/4 in Weldon | > KBU 35 PQ | > AKBU 35 PMQW 18 V AS |
| > KBM 65 UQW | > AKBU 35 PMQW 18 V AS | Set 1x 12 Ah |
| > KBM 50 UQW | Construction-Site 1x 12 Ah Set con attacco Weldon da 3/4 in / HSS NOVA 50 | > AKBU 35 PMQW 18 V AS |
| > KBU 35 QW Fabricator M12 Tapping-Set 3/4 in Weldon | > AKBU 35 PMQW 18 V AS | Set 2x 8 Ah |
| | Construction-Site 2x 8 Ah | > AKBU 35 PMQW AS |
| | | > AKBU 35 PMQ AS |



Automatic

> KBM 50 auto QW

> KBM 50 auto