



FEIN



Fresa a corona HSS Dura 25 con attacco QuickIN

Rivestimento superficiale TiN per una lunga durata e una migliore scorrevolezza.

Misure metriche, profondità di taglio 25 mm.

35,80 € senza IVA

Numero d'ordine: 6 31 33 120 06 7

Specifiche tecniche

SPECIFICHE GENERALI

Profondità di taglio

25 mm

Ø foro

12 mm

Adatto per le seguenti macchine

Universal

- | | | |
|-------------------------|---------------------------|---------------------------|
| > KBM 65 U | > KBU 35 PQW | Ah Set con attacco |
| > KBM 65 UQW | > KBU 35-2 QW | Weldon da 3/4 in / HSS |
| > AKBU 35 PMQ AS | > KBU 35 MQW | NOVA 50 |
| > KBM 50 Q | > KBU 35 QW | > AKBU 35 PMQW AS |
| > KBM 50 UQW | > KBU 35-2 Q | Construction-Site Set con |
| > KBU 35 QW Fabricator | > KBU 35 MQ | attacco Weldon da 3/4 in |
| M12 Tapping-Set 3/4 in | > KBU 35 Q | / HSS NOVA 50 |
| Weldon | > AKBU 35 PMQW 18 V AS | > AKBU 35 PMQW 18 V AS |
| > KBU 35 QW Structural | Construction-Site 2x 8 Ah | Set 1x 12 Ah |
| Steel-Set 3/4 in Weldon | Set con attacco Weldon | > AKBU 35 PMQW 18 V AS |
| > KBM 50 U | da 3/4 in / HSS NOVA 50 | Set 2x 8 Ah |
| > KBU 35 PQ | > AKBU 35 PMQW 18 V AS | > AKBU 35 PMQW AS |
| | Construction-Site 1x 12 | |

Automatic

- | | |
|------------------|---------------|
| > KBM 50 auto QW | > KBM 50 auto |
|------------------|---------------|